



General Information					
Kit Part Number: <u>2-2</u>	<u>2110838-8</u>				
Description: Pre	Pre-Insulated Short Spring Spade Tongue Terminals Kit				
Application: HV	HVAC Systems, Instrumentation and Controls, Lighting Applications, Motors, Panel Boxes, Power Supplies,				
Sw	vitchgear, Transportation				
Family: PL/	ASTI-GRIP				
TE Brand: AM	/IP Products				
Solution: MR	RO (Maintenance, Repair and Operation)				
Product Type: Ter	rminals & Splices				
Number of Pieces: 120	0				
RoHS: Yes	s				
Specifications					
Body and Plating: Tin	n Plated, Phosphor Bronze and Brass				
Insulation: Vin	nyl				
Stud/Tab Size: 4, 6	6, 8, 10				
Temperature Rating: 90	Degrees C (Max)				
Terminal Type: Sho	ort Spring Spade Tongue				
Tool Included: No					
Voltage Rating: 600	ov				
Wire Gauge (AWG): 12-	-10, 16-14 , 22-16				
Product Highlights					

Product Highlights

Pre-insulated PLASTI-GRIP solderless terminals and splices are designed specifically to answer the need for inexpensive, insulated electrical terminations. They can be used in almost every type of commercial application and accommodate wire sizes from 22 AWG through 2/0 AWG. Carefully engineered application tooling has been developed to ensure uniformly high quality terminations. Tool and terminal have been designed as a team to promote ease and speed of application and at the same time to provide precise crimping pressure for every wire size. The wire and the terminal barrel form a homogeneous mass of metal, providing a connection of maximum conductivity, tensile strength, and high resistance to corrosion. The quality performance, the facility of installation and the inherent simplicity make them ideal for many industrial applications. PLASTI-GRIP products are available as rings, spades, flanged spaded, slotted rings, splices and several other varieties. Wire ranges for the terminals and splices are 22 AWG through 2/0 and stud sizes from #2 through 3/8".

Features and Benefits

- Vinyl insulation sleeve provides good dielectric strength and supports the wire insulation so that no bare wire is exposed
- Most product rated to 90 degrees C, with an operating voltage of 600 V
- Insulation is 94V-0 rated
- Funneled wire entry on terminal prevents turned back wire strands and permits rapid wire insertion during high speed production
- Serrations in the crimp barrel provide maximum contact and tensile strength after crimping

Applications

- HVAC
- Instruments / Controls
- Lighting
- Switchgear





- Power Supplies
- Panel Boxes
- Transportation
- Motors





Bill of Materials

Part No.	Qty In Kit	Description	Datasheet	P/N Details	Search Distributors Inventory
<u>53247-1</u>	10	Short Spring Spade AWG 12-10, Stud 8		<u>Details</u>	<u>Search</u>
<u>52950</u>	10	Short Spring Spade AWG 22-16, Stud 8		<u>Details</u>	<u>Search</u>
<u>53246-1</u>	10	Short Spring Spade AWG 12-10, Stud 6		Details	<u>Search</u>
<u>52947</u>	10	Short Spring Spade AWG 22-16, Stud 4		Details	<u>Search</u>
<u>53242-1</u>	10	Short Spring Spade AWG 22-16, Stud 10		Details	<u>Search</u>
<u>52949</u>	10	Short Spring Spade AWG 22-16, Stud 6		Details	<u>Search</u>
<u>53248-1</u>	10	Short Spring Spade AWG 12-10, Stud 10		Details	<u>Search</u>
<u>52963-4</u>	10	Short Spring Spade AWG 12-10 Stud 10		<u>Details</u>	<u>Search</u>
<u>52957-1</u>	10	Short Spring Spade AWG 16-14, Stud 10		Details	<u>Search</u>
<u>52955</u>	10	Short Spring Spade AWG 16-14, Stud 6		<u>Details</u>	<u>Search</u>
<u>53244-1</u>	20	Short Spring Spade AWG 16-14, Stud 8		<u>Details</u>	<u>Search</u>

Recommended Tool

Part No.

Included in Kit

















