

High-precision sockets for DIL-IC

SMD-socket for DIL IC

Contacts, especially integrated into the insulating part, will adjust to the solder paste which possibly is not equally distributed.

	art. no.	no. of contacts	dim. [mm]			
			A	B	C	D
DIL 16 SMD M	16		20.10	10.10	7.62	3.50
DIL 20 SMD M	20		25.20	10.10	7.62	3.50
DIL 24 03 SMD M	24		30.30	10.10	7.62	3.50
DIL 28 SMD M	28		35.40	17.60	15.24	11.20

contact shell surface: tin-plated

contact spring: gold-plated

SMD-plug for DIL

with PK 3-contacts

	art. no.	no. of contacts	dim. [mm]			
			A	B	C	D
DIL 08 SMD PK3 ...	8		10.00	10.10	7.62	3.50
DIL 16 SMD PK3 ...	16		20.10	10.10	7.62	3.50
DIL 20 SMD PK3 ...	20		25.20	10.10	7.62	3.50
DIL 24 SMD PK3 ...	24		30.30	17.60	15.24	11.70
DIL 28 SMD PK3 ...	28		35.40	17.60	15.24	11.20
DIL 40 SMD PK3 ...	40		50.70	17.60	15.24	12.00
please indicate:		... surface G = gold-plated Z = tin-plated				