

DATA SHEET

Class 2, Y5V 10 V Surface-mount ceramic multilayer capacitors

Product specification
Supersedes data of 24th May 2000

2001 May 30 Rev.5

Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

FEATURES

- Three standard sizes
- High capacitance per unit volume
- Supplied in tape on reel or in bulk case
- NiSn terminations.

APPLICATIONS

Consumer electronics, for example:

- Tuners
- Television receivers
- Video recorders
- All types of cameras.

DESCRIPTION

The capacitor consists of a rectangular block of ceramic dielectric in which a number of interleaved metal electrodes are contained. This structure gives rise to a high capacitance per unit volume.

The inner electrodes are connected to the two terminations and finally covered with a layer of plated tin (NiSn). A cross section of the structure is shown in Fig.1.

QUICK REFERENCE DATA

| DESCRIPTION | VALUE |
|--|---|
| Rated voltage U_R (DC) | 10 V |
| Capacitance range (E6 series) | 1.0 to 10 μ F; note 1 |
| Tolerance on capacitance after 1 000 hours | -20% to +80% (Z) |
| Test voltage (DC) for 1 minute | $2.5 \times U_R$ |
| Sectional specifications | IEC 60384-10, second edition 1989-04; also based on CECC 32 100 |
| Detailed specification | based on CECC 32 101-801 |
| End terminations | NiSn |
| Climatic category (IEC 60068) | 25/085/21 |

Note

1. Measured at 25 °C, 1 V and 1 kHz, using a four-gauge method.





Fig.1 Construction of a ceramic multilayer capacitor.

Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

MECHANICAL DATA



For dimensions see Table 1.

Fig.2 Component outline.

Physical dimensions

Table 1 Capacitor dimensions

| CASE SIZE | L ₁ | W | T | | L ₂ and L ₃ | | L ₄ MIN. |
|----------------------------------|----------------|--------------|-------|-------|-----------------------------------|-------|------------------------|
| | | | MIN. | MAX. | MIN. | MAX. | |
| Dimensions in millimetres | | | | | | | |
| 0603 | 1.6 ±0.10 | 0.8 ±0.07 | 0.73 | 0.87 | 0.25 | 0.65 | 0.40 |
| 0805 | 2.0 ±0.1 | 1.25 ±0.1 | 0.50 | 1.35 | 0.25 | 0.75 | 0.55 |
| 1206 | 3.2 ±0.15 | 1.6 ±0.15 | 0.50 | 1.75 | 0.25 | 0.75 | 1.40 |
| Dimensions in inches | | | | | | | |
| 0603 | 0.063 ±0.004 | 0.032 ±0.003 | 0.029 | 0.035 | 0.010 | 0.026 | 0.016 |
| 0805 | 0.079 ±0.004 | 0.049 ±0.004 | 0.020 | 0.053 | 0.010 | 0.030 | 0.022 |
| 1206 | 0.126 ±0.006 | 0.063 ±0.006 | 0.020 | 0.069 | 0.010 | 0.030 | 0.056 |

Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

SELECTION CHART FOR 10 V

| C (nF) | LAST TWO DIGITS OF 12NC | 10 V | | | |
|-----------|----------------------------|---|------------|------------|------------|
| | | 0603 | 0805 | 1206 | |
| 1000 | 63 | 0.8 ±0.07 | | 0.85 ±0.10 | |
| 1500 | 65 | | | | |
| 2200 | 67 | | | | |
| 3300 | 69 | | 1.25 ±0.10 | 1.15 ±0.10 | |
| 4700 | 72 | | | | |
| 6800 | 74 | Values in shaded cells indicate thickness classification. | | | 1.60 ±0.15 |
| 10000 | 76 | | | | |

Thickness classification and packing quantities

| THICKNESS CLASSIFICATION (mm) | 8 mm TAPE WIDTH QUANTITY PER REEL | | | | QUANTITY PER BULK CASE | |
|-------------------------------------|--------------------------------------|---------|--------------|---------|---------------------------|------|
| | Ø180 mm; 7" | | Ø330 mm; 13" | | 0603 | 0805 |
| | PAPER | BLISTER | PAPER | BLISTER | | |
| 0.8 ±0.07 | 4000 | – | 15000 | – | 15000 | – |
| 0.85 ±0.10 | 4000 | – | 15000 | – | – | – |
| 1.15 ±0.10 | – | 3000 | – | 10000 | – | – |
| 1.25 ±0.10 | – | 3000 | – | 10000 | – | 5000 |
| 1.60 ±0.15 | – | 2500 | – | 7000 | – | – |

Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

ORDERING INFORMATION


Components may be ordered by using either a simple 15-digit clear text code or Phycomp's unique 12NC.

Clear text code

Example: 06032F105Z24BB0D

| SIZE CODE | TEMP. CHAR. | CAPACITANCE | TOL. | VOLTAGE | TERMINATION | PACKING | MARKING | SERIES |
|----------------------|-------------|--|---------------|----------|-------------|---|---|---------|
| 0603 0805 1206 | 2F = Y5V | 105 = 1 000 000 pF; the third digit signifies the multiplying factor: 5 = × 100 000 6 = × 1 000 000 | Z = -20%/+80% | 6 = 10 V | B = NiSn | 2 = 180 mm; 7" paper 3 = 330 mm; 13" paper B = 180 mm; 7" blister F = 330 mm; 13" blister P = bulk case | 0 = no marking 2 = 2-character marking in North America only | D = BME |

Ordering code 12NC



Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

ELECTRICAL CHARACTERISTICS

Class 2 capacitors; Y5V dielectric; NiSn terminations

Unless otherwise stated all electrical values apply at an ambient temperature of 25 ± 1 °C, an atmospheric pressure of 86 to 105 kPa, and a relative humidity of 63 to 67%.

| DESCRIPTION | VALUE |
|---|-------------------------------------|
| Capacitance range (E6 series); note 1. | 1.0 to 10 μ F |
| Tolerance on capacitance after 1000 hours | -20% to +80% (Z) |
| Tan δ ; note 1. | $\leq 12.5\%$ |
| Insulation resistance after 1 minute at U_R (DC) | $R_{ins} \times C \geq 500$ seconds |
| Maximum capacitance change as a function of temperature | +30% to -80% |
| Ageing | typical 7% per time decade |
| Resistance to soldering heat | 260 °C; 10 seconds |

Note

1. Measured at 25 °C, 1 V and 1 kHz, using a four-gauge method.

Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

TESTS AND REQUIREMENTS

Table 2 Test procedures and requirements

| IEC 60384-10/ CECC 32 100 CLAUSE | IEC 60068-2 TEST METHOD | TEST | PROCEDURE | REQUIREMENTS |
|---|----------------------------------|---------------------------------------|--|---|
| 4.4 | | mounting | the capacitors may be mounted on printed-circuit boards or ceramic substrates by applying wave soldering, reflow soldering (including vapour phase soldering) or conductive adhesive | no visible damage |
| 4.5 | | visual inspection and dimension check | any applicable method using $\times 10$ magnification | in accordance with specification |
| 4.6.1 | | capacitance | $f = 1 \text{ kHz}$; Y5V measuring voltage $1 V_{\text{rms}}$ at $25 \text{ }^\circ\text{C}$ | within specified tolerance |
| 4.6.2 | | $\tan \delta$ | $f = 1 \text{ kHz}$; Y5V measuring voltage $1 V_{\text{rms}}$ at $25 \text{ }^\circ\text{C}$ | in accordance with specification |
| 4.6.3 | | insulation resistance | at U_R (DC) for 1 minute | in accordance with specification |
| 4.6.4 | | voltage proof | $2.5 \times U_R$ for 1 minute | no breakdown or flashover |
| 4.7.1 | | temperature characteristic | between minimum and maximum temperature | in accordance with specification |
| 4.8 | | adhesion | a force of 5 N applied for 10 s to the line joining the terminations and in a plane parallel to the substrate | no visible damage |
| 4.9 | | bond strength of plating on end face | mounted in accordance with CECC 32 100, paragraph 4.4 | no visible damage |
| | | | conditions: bending 1 mm at a rate of 1 mm/s, radius jig. 340 mm | $\Delta C/C: \leq 30\%$ |
| 4.10 | Tb | resistance to soldering heat | precondition: $120 \text{ to } 150 \text{ }^\circ\text{C}$ for 1 minute; $260 \pm 5 \text{ }^\circ\text{C}$ for $10 \pm 0.5 \text{ s}$ in a static solder bath | the terminations shall be well tinned after recovery $\Delta C/C: \pm 20\%$ $\tan \delta$: original specification R_{ins} : original specification |
| | | resistance to leaching | $260 \pm 5 \text{ }^\circ\text{C}$ for $30 \pm 1 \text{ s}$ in a static solder bath | using visual enlargement of $\times 10$, dissolution of the terminations shall not exceed 10% |
| 4.11 | Ta | solderability | zero hour test, and test after storage (20 to 24 months) in original packing in normal atmosphere; unmounted chips completely immersed for $2 \pm 0.5 \text{ s}$ in a solder bath at $235 \pm 5 \text{ }^\circ\text{C}$ | the terminations shall be well tinned |

Surface-mount ceramic multilayer capacitors

Class 2, Y5V 10 V

| IEC 60384-10/ CECC 32 100 CLAUSE | IEC 60068-2 TEST METHOD | TEST | PROCEDURE | REQUIREMENTS |
|---|----------------------------------|-------------------------------|---|--|
| 4.12 | Na | rapid change of temperature | preconditioning: -25 to +85 °C; 5 cycles | no visible damage after 48 hours recovery: $\Delta C/C: \leq 20\%$ |
| 4.14 | Ca | damp heat, steady state | preconditioning (thermal treatment): 500 ±12 hours at 40 °C; 90 to 95% RH | no visual damage after 48 hours recovery: $\Delta C/C: +30\%/-40\%$ $\tan \delta: \leq 15\%$ $R_{ins}: 500 M\Omega$ or $R_i C_R \geq 25 s$, whichever is less |
| | | damp heat, with U_R load | initialization: 48 hours after U_R at 40 °C for 1 hour (for initial value measurement); 500 ±12 hours at 40 °C; 90 to 95% RH; U_R applied | pretreatment: U_R at 40 °C for 1 hour after 48 hours recovery: $\Delta C/C: +30\%/-40\%$ $\tan \delta: \leq 15\%$ $R_{ins}: 500 M\Omega$ or $R_i C_R \geq 25 s$, whichever is less |
| 4.15 | | endurance | initialization: $2 \times U_R$ at 85 °C for 1 hour (initial value is measured after 48 hours, recovery at room temperature); 1 000 hours at 85 °C and $2 \times U_R$ applied | pretreatment: U_R at 40 °C for 1 hour after 48 hours recovery: $\Delta C/C: +30\%/-40\%$ $\tan \delta: \leq 15\%$ $R_{ins}: 1000 M\Omega$ or $R_i C_R \geq 50 s$, whichever is less |

**Surface-mount ceramic
multilayer capacitors**

Class 2, Y5V 10 V

REVISION HISTORY

| Revision | Date | Change Notification | Description |
|-----------------|-------------|--------------------------------|------------------------------|
| Rev.5 | 2001 May 30 | – | - Converted to Phycomp brand |
| | | | |