

For more Information  
please call

1-800-Belden1



### General Description:

RG-402/U type, 19 AWG solid .036" silver-plated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield (100% coverage), unjacketed.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	19	Solid	SPCCS - Silver Plated Copper Covered Steel	0.9144

Total Number of Conductors: 1

#### Insulation

##### Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (mm)
Teflon®	TFE - Tetrafluoroethylene	2.9464

#### Outer Shield

##### Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Tape	Copper Foil	100
2	Braid	Tin-Filled Composite	100

#### Overall Cable

Overall Nominal Diameter: 3.505 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +200°C

UL Temperature Rating: 105°C

Non-UL Temperature Rating: 200°C

Bulk Cable Weight: 38.693 Kg/Km

Max. Recommended Pulling Tension: 311.374 N

Min. Bend/Installation: 6.350 mm

Min. Bend Radius (Overall): 38.100 mm

Min. Flexing Radius: 1.905 cm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

AWM Specification: UL Style 10245

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2005

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	402/U

### Flame Test

Other Flame Test:	Horizontal Wire
-------------------	-----------------

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
50

### Nom. Inductance:

Inductance (µH/m)
0.22967

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
96.7895

### Nominal Velocity of Propagation:

VP (%)
69.5

### Nominal Delay:

Delay (ns/m)
4.79026

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
67.2605

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
14.7645

### Maximum VSWR:

Description	Freq. (MHz)	Max. VSWR
Ramp Function, End Points	500	1.1
	20000	1.3

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
500	26.248
1000	39.372
2000	59.3861
3000	75.1349
5000	101.711
7000	124.022
10000	152.895
15000	193.907
18000	215.89
20000	229.67

### Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
-------------	-----------------------

500	31.1695
1000	47.5745
3000	86.9465
5000	118.116
10000	177.174
20000	275.604

**Nom. Power Rating:**

Freq. (MHz)	Rating (W)
500	600
1000	401
2000	268
3000	211
5000	157
7000	129
10000	105
15000	83
18000	74
20000	70

**Max. Operating Voltage - UL:**

<b>Voltage</b>
30 V RMS

**Max. Operating Voltage - Non-UL:**

<b>Voltage</b>
1900 V RMS

**Misc. Information (Overall)**

**Notes (Overall)**

**Notes:** Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1673A TIN100	30 MT	1.406 KG	TIN - COLOR	C	#19 TFE BRD TINNED COAX
1673A TIN250	76 MT	3.289 KG	TIN - COLOR	C V	#19 TFE BRD TINNED COAX
1673A TIN50	15 MT	0.816 KG	TIN - COLOR		#19 TFE BRD TINNED COAX
1673A TIN500	152 MT	6.350 KG	TIN - COLOR		#19 TFE BRD TINNED COAX

**Notes:**

C = CRATE REEL PUT-UP.

V = 250' PUT-UP EXACT LENGTH MAXIMUM OF 3 PIECESMINIMUM LENGTH 50'500' PUT-UP EXACT LENGTH MAXIMUM OF 5 PIECESMINIMUM LENGTH 50'

Revision Number: 3    Revision Date: 08-07-2013

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.