3M™ Multi-Touch Display M2467PW

Sophistication Meets Innovation

The 24-inch **3M**[™] **Multi-Touch Display M2467PW** takes interactive display technology to the next level by combining uncompromising multi-touch performance, brilliant high-definition graphics, wide viewing angles and elegant product design into a fully-integrated, easy-to-use, plug-and-play multi-touch desktop device.

Inspired by the industrial design influence of modern consumer devices, the M2467PW display features a stylish flat front surface design that makes it an attractive addition to any professional or retail environment. Beyond contemporary aesthetics, the M2467PW display is designed to meet the unique demands of multi-touch use by featuring a 3M-proprietary antistiction surface treatment that allows a user's fingers to effortlessly glide across the screen. The display also features a sturdy and robust base that easily accommodates a full 90-degree position range for more viewing flexibility. With an active touch area of over 246 square inches, the M2467PW display gives users 25% more touch area than a typical 21.5" touch monitor and provides an inviting horizontal surface for multi-user on screen collaboration. With a standard 100mm x 100mm VESA mount, this display allows for versatile integration onto a wall, swinging arm or other open surfaces.

The M2467PW display features 3M's industry-leading Projected Capacitive (3M PCT) technology that exceeds the typical touch performance of popular smart phone and tablet devices by offering a high performance multi-touch experience. Recognizing up to 20 simultaneous touch events, each at a 6-millisecond response rate, the M2467PW display also recognizes and rejects the user's palms or arm resting on the screen to help prevent inadvertent touches. This incredible touch performance allows for a more natural user interaction that results in a truly inspired creative experience unrivaled by competitive touch displays.

Complementing the M2467PW display's stylish industrial design and exceptional multi-touch performance is an 1080p full HD LCD that displays dynamic, vivid and realistic images essential for creating high impact and engaging user applications. The M2467PW display is LED backlit which not only reduces power consumption, but also offers enhanced brightness,



Recommended Multi-Touch Applications

- Computer Aided Design
- Interactive Point-of-Purchase
- Virtual Concierge
- Software Development
- Assisted Selling
- Trade Show/Convention
- Simulation Training
- Security Management
- Telepresence
- · Control Room
- Healthcare

better contrast levels, and more consistent light output as compared to typical CCFL displays. The M2467PW display is able to maintain superior image quality even when viewed at off angles, due to its impressive 178 degree vertical and horizontal viewing angles.

By combining industry-leading multi-touch performance, vibrant high-definition graphics, and wide viewing angles with a fully integrated, industrial-design desktop device, the 3M Multi-Touch Display M2467PW clearly defines the next level of interactive touch displays. Sophistication has met innovation.

Feature	Benefit	
3M PCT Multi-Touch Technology	 20-touch multi-touch performance for intuitive on-screen collaboration Ultra-fast 6 ms touch response time for advanced multi-touch applications Palm rejection creates natural user operation when using one or two hands Superior touch accuracy (99% of true position) enables precise touch performance, even at display edge and corners 	
High Performance 1080p HD LCD with LED Backlight	 Vivid realistic images with enhanced brightness and contrast levels creates high-impact on-screen interactive experience Wide viewing angle for viewing flexibility while maintaining image quality Provides improved power efficiency and reduced consumption 	
Sophisticated Flat Front Surface Design	 Provides the elegant and modern aesthetics of popular portable consumer devices Anti-stiction surface provides improved usability for multi-touch applications Easy-to-clean surface without bezels Eliminates dust and debris build up at the edge and corners of the display 	



3M™ Multi-Touch Display M2467PW Specifications

Functional Specifications

Display Details

LCD Technology	P-MVA (premium multi-domain vertical alignment)	
Backlight	LED	
Aspect Ratio	16:9	
Display Colors	16.7 Million	
Pixel Pitch	0.277 mm x 0.277 mm	
Brightness with touch sensor (1)	250 cd/m2 (nit) (typical) 217 cd/m2 (nit)	
Contrast Ratio (2)	5000:1 typical	
Viewing Angle	Horizontal/Vertical: 178 degrees typical	
Video Response Time (3)	16 milliseconds (typical)	
Control Type	OSD with capacitive buttons	
Native Resolution	1920 x 1080 (Full HD)	

- (1) Brightness measured on a display with 3M[™] Projected Capacitive sensor.
- (2) Measured at a contrast ratio of 10.
- (3) Gray to Gray

Touch Details

Number of Inputs	20 inputs with palm rejection
Touch Point Speed	6 ms
Input Type	Finger, Thin Glove
Touch Communication	USB
Operating System Support	Windows7/Vista/XP, Linux, Mac

Physical Specifications

Product Details

Operating Environment	0 to +40 degrees C
	Relative Humidity, non-condensing 90%
Storage Environment	-10 to +60 degrees C (anticipated)
Video Input	HDMI, VGA, Display Port
Multimedia	Audio input, 3 watt audio speaker
VESA Pattern	100mm x 100mm, 100mm x 200mm
Power Supply	External, 110/220 VAC Power Supply
Power Consumption	44.5 watts (maximum)
RoHS Compliant	Yes
Agency Approvals	FCC-B, CE, TUV, C-Tick
Warranty	1 year on touch display

Dimensions and Weight


-	
Physical (WxHxD)	576 x 432 x 250 mm
	22.7 x 17.0 x 9.8 inches
Display Area (WxH)	531.4 x 298.9 mm
(viewing area)	20.9 x 11.8 in
Packaging (WxHxD)	632 x 538 x 291 mm
	24.9 x 21.2 x 11.5 inches
Display Weight	6.6 Kg / 14.6 lbs
Packaging/Display Weight	8.4 Kg /18.5 lbs

Ordering Information

Part Number	98-0003-3786-9	



90-degrees of Adjustment



Flat Front Surface (Virtual Bezel)



Connections

3M Touch Systems

Subsidiary of 3M Company 501 Griffin Brook Park Drive Methuen, MA 01844 U.S.A.

1-888-659-1080 www.3M.com/touch RoHS Directive compliant: In accordance with European Directive 2002/95/EC, "RoHS Directive compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M. (9/06)

IMPORTANT NOTICE TO PURCHASER: Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. 3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software mediator to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. 3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/102)



© 3M 2012 All Rights Reserved. 3M is a trademark of 3M Company. M2467PW-0312

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

3M:

M2467PW