

GNM3145C1H221KD01#

"#" indicates a package specification code.

Discontinued General 125 Reflow RoHS

< List of part numbers with package codes > GNM3145C1H221KD01D , GNM3145C1H221KD01J

Shape

| $\begin{array}{c} P \\ B \\ T \\ C \\ C$ | 8885 |
|---|--------------|
| L size | 3.2 ± 0.15mm |
| W size | 1.6 ± 0.15mm |
| T size | 0.8 ± 0.1mm |
| Distance between external terminals P | 0.8 ± 0.1mm |
| Size code in inch(mm) | 1206 (3216) |

Specifications

| Capacitance | 220pF ±10% |
|--|------------|
| Rated voltage | 50Vdc |
| Temperature characteristics (complied standard) | COG(EIA) |
| Temperature coefficient | 0 ± 30ppm/ |
| Temperature range of temperature characteristics | 25 to 125 |
| Operating temperature range | -55 to 125 |

| References | 3 | |
|------------|--------------------|------------------|
| Packaging | Specifications | Minimum quantity |
| D | 180mm Paper taping | 4000 |
| J | 330mm Paper taping | 10000 |

| Mass (typ.) | |
|-------------|------|
| 1 piece | 26mg |
| 180mm Reel | 214g |

1 of 1

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2014/10/19