

GRM32ER60J476ME20#

" # " indicates a package specification code.

Available

General

85℃



Reflow OK

RoHS

REACH

< List of part numbers with package codes >
GRM32ER60J476ME20L , GRM32ER60J476ME20K

Shape



| | |
|---------------------------------------|-------------|
| L size | 3.2 ± 0.3mm |
| W size | 2.5 ± 0.2mm |
| T size | 2.5 ± 0.2mm |
| External terminal width e | 0.3mm min. |
| Distance between external terminals g | 1.0mm min. |
| Size code in inch(mm) | 1210 (3225) |

References

| Packaging | Specifications | Minimum quantity |
|-----------|-----------------------|------------------|
| L | 180mm Embossed taping | 1000 |
| K | 330mm Embossed taping | 4000 |

| Mass (typ.) | |
|-------------|-------|
| 1 piece | 110mg |
| 180mm Reel | 168g |

Specifications

| | |
|--|------------|
| Capacitance | 47μF ± 20% |
| Rated voltage | 6.3Vdc |
| Temperature characteristics (complied standard) | X5R(EIA) |
| Capacitance change rate | ± 15.0% |
| Temperature range of temperature characteristics | -55 to 85 |
| Operating temperature range | -55 to 85 |

⚠ Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.