



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE74157
Integrated Circuit
TTL – Quad 2-Line-to-1-Line Data Selector/Demultiplexer

Description:

The NTE74157 is a quad 1-line-to-4-line data selector/multiplexer in a 16-Lead plastic DIP type package that contains inverters and drivers to supply full on-chip data selection to the four output gates. A separate strobe input is provided. A 4-bit word is selected from one of two sources and is routed to the four outputs. The NTE74157 presents true data outputs to minimize propagation delay time.

Features:

- Buffered Inputs and Outputs

Applications:

- Expand Any Data Input Point
- Multiplex Dual Data Buses
- Generate Four Functions of Two variables (One Variable is Common)
- Source Programmable Counters

Absolute Maximum Ratings: (Note 1)

Supply Voltage, V_{CC}	7V
DC Input Voltage, V_{IN}	5.5V
Power Dissipation, P_D	150mW
Operating Temperature Range, T_A	0°C to +70°C
Storage Temperature Range, T_{STG}	-65°C to +150°C

Note 1. Unless otherwise specified, all voltages are referenced to GND.

Recommended Operating Conditions:

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	4.75	5.0	5.25	V
High-Level Output Current	I_{OH}	-	-	-800	μA
Low-Level Output Current	I_{OL}	-	-	16	mA
Operating Temperature Range	T_A	0	-	+70	°C

Electrical Characteristics: (Note 2, Note 3)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
High Level Input Voltage	V_{IH}		2	-	-	V
Low Level Input Voltage	V_{IL}		-	-	0.8	V
Input Clamp Voltage	V_{IK}	$V_{CC} = \text{MIN}$, $I_I = -12\text{mA}$	-	-	-1.5	V
High Level Output Voltage	V_{OH}	$V_{CC} = \text{MIN}$, $V_{IH} = 2\text{V}$, $V_{IL} = 0.8\text{V}$, $I_{OH} = -800\mu\text{A}$	2.4	3.4	-	V
Low Level Output Voltage	V_{OL}	$V_{CC} = \text{MIN}$, $V_{IH} = 2\text{V}$, $V_{IL} = 0.8\text{V}$, $I_{OL} = 4\text{mA}$	-	0.2	0.4	V
Input Current	I_I	$V_{CC} = \text{MAX}$, $V_I = 5.5\text{V}$	-	-	1	mA
High Level Input Current	I_{IH}	$V_{CC} = \text{MAX}$, $V_I = 2.4\text{V}$	-	-	40	μA
Low Level Input Current	I_{IL}	$V_{CC} = \text{MAX}$, $V_I = 0.4\text{V}$	-	-	-1.6	mA
Short-Circuit Output Current	I_{OS}	$V_{CC} = \text{MAX}$, Note 4	-18	-	-55	mA
Supply Current	I_{CC}	$V_{CC} = \text{MAX}$, Note 5	-	30	48	mA

Note 2. For conditions shown as MIN or MAX, use the appropriate value specified under "Recommended Operation Conditions".

Note 3. All typical values are at $V_{CC} = 5\text{V}$, $T_A = +25^\circ\text{C}$.

Note 4. Not more than one output should be shorted at a time and duration of short-circuit should not exceed one second.

Note 5. I_{CC} is measured with 4.5V applied to all inputs and all outputs open.

Switching Characteristics: ($V_{CC} = 5\text{V}$, $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Propagation Delay Time (From Data Inputs to Y Output)	t_{PLH}	$R_L = 400\Omega$, $C_L = 15\text{pF}$	-	9	14	ns
	t_{PHL}		-	9	14	ns
Propagation Delay Time (From Strobe \bar{G} Input to Y Output)	t_{PLH}		-	13	20	ns
	t_{PHL}		-	14	21	ns
Propagation Delay Time (From Select A/B Input to Y Output)	t_{PLH}		-	15	23	ns
	t_{PHL}		-	18	27	ns

Function Table:

Inputs				Output
Strobe \bar{G}	Select A/B	A	B	Y
H	X	X	X	H
L	L	L	X	H
L	L	H	X	L
L	H	X	L	H
L	H	X	H	L

H = HIGH Level

L = LOW Level

X = Don't Care

Pin Connection Diagram

