


REQUIREMENTS

- 1- CLIP FOR T0218/T0220
- 2- FORCE MIN. AT S: 4.5 mm = 10 N
- 3- FORCE MIN. AT S: 5.0 mm = 12 N



SCALE 1 : 1

Important dimensions

Note:		Scale							
THIS DOCUMENT CONTAINS AVID THERMALLOY'S INTELLECTUAL PROPERTY WHICH IS SUPPLIED IN CONFIDENCE; IT MUST NOT BE USED FOR ANY PURPOSE OTHER THAN WHICH IT IS SUPPLIED; IT MUST NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION FROM THE OWNERS		4 : 1							
AAVID THERMALLOY EUROPE www.aavidthermalloy.com Via XXV Aprile, 32 40057 Cadrano - Bologna ITALY Tel. +39 051 764011 Fax +39 051 764090 Cheney Manor SWINDON WILTS SN2 2QN UK Tel. +44 1793 401400 Fax +44 1793 615396 <small>COMPANY WITH QUALITY SYSTEM CERTIFIED BY LRQA ISO 9001:2000</small>		1							
		Format A4	REV	Date	Revision description				
		Die n.	MATERIAL EN10132-4 C67S 0.4x14.5		DRAWING n. 439651				
		Factor	GENERAL TOLERANCES		Vis. n.				
		Perim.	Machining ± 1 mm		Drawn <i>R. Tassinari</i>		Description: CLIP-STEEL-14.5x21x0.4-ZH ROHS COMPLIANT- (4597G)		
		Area	FINISH Zn high resistance plated RoHS Compliant		Check				
		Weight	Corrosion resistance: 50 h Neutral salt						