

Ring Terminal T&B Catalog Number:

RC10-14

UPC Number: 78621080442

Status: Active

Description:

Insulated Nylon Ring Terminal For Wire Range 12-10 Stud Size 1/4, Yel-

low




US Cutsheet PDF Catalog Link http://www-public.tnb.com/contractor/docs/

stakon.pdf

Features

Self-insulated with high dieletric-strength nylon sleeves. An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and

eliminates conductor creep.



	omminates sorialists or sop.
General	
Insulation Type	Insulated Nylon
Terminal Series	RC
Material	Copper
Finish	Electro -Tin Plated
Color	Yellow
Wire Range	12-10
Stud Size	1/4
Dimension Information	
Maximum Insulation (inches)	.210
Stock Thickness	.04
A (inches)	1.12
B (inches)	.53
C (inches)	.32
M (inches)	.86
Specifications	
Temperature Rating	105°C
Voltage Rating	600V
Flammability Rating	UL 94 V-2
Tooling	
Tool Charts	Available on Website
Application Tools	WT2000, WT112M, WT145C, ERG4001,
••	ERG4003, WT145A
Recommended Tool	ERG4001
Packaging	
T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	250
Package Type	Standard
T&B Sold in UOM	Each
T&B Weight Per UOM	6.25 lbs. per 1000
Alternate Package Qty	RC713
Application Support	
T&B Sales Drawings	wsd-000269



Overview	Available on Website
Wire Guide Tables	Available on Website
Certifications	
RoHS Compliance	Yes
Certifications	





File Nbr: E9809