

THV SERIES

125°C Low ESR, Lead Free Reflow Soldering.

◆FEATURES

- Load Life : 125°C 2000~3000 hours Low ESR.
- Lead free reflow soldering is available.
- Available for high density mounting.
- RoHS compliance.



◆SPECIFICATIONS

Items	Characteristics																
Category Temperature Range	-40~+125℃																
Rated Voltage Range	16~50V.DC																
Capacitance Tolerance	±20% (20℃,120Hz)																
Leakage Current(MAX)	I=0.01CV or 3μA whichever is greater.(After 2 minutes application of rated voltage) I=Leakage Current(μA) C=Capacitance(μF) V=Rated Voltage(V)																
Dissipation Factor(MAX) (tanδ)	<table><tr><td>Rated Voltage (V)</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>tanδ</td><td>0.23</td><td>0.18</td><td>0.16</td><td>0.14</td></tr></table> (20℃,120Hz)					Rated Voltage (V)	16	25	35	50	tanδ	0.23	0.18	0.16	0.14		
Rated Voltage (V)	16	25	35	50													
tanδ	0.23	0.18	0.16	0.14													
Endurance	After life test with rated ripple current at conditions stated in the teble below at 125℃, the capacitors shall meet the following requirements. <table><tr><td>Capacitance Change</td><td>Within ±30% of the initial value.</td><td>Case Size</td><td>LifeTime (hrs)</td></tr><tr><td>Dissipation Factor</td><td>Not more than 300% of the specified value.</td><td>φD=6.3</td><td>2000</td></tr><tr><td>Leakage Current</td><td>Not more than the specified value.</td><td>φD≥8</td><td>3000</td></tr></table>					Capacitance Change	Within ±30% of the initial value.	Case Size	LifeTime (hrs)	Dissipation Factor	Not more than 300% of the specified value.	φD=6.3	2000	Leakage Current	Not more than the specified value.	φD≥8	3000
Capacitance Change	Within ±30% of the initial value.	Case Size	LifeTime (hrs)														
Dissipation Factor	Not more than 300% of the specified value.	φD=6.3	2000														
Leakage Current	Not more than the specified value.	φD≥8	3000														
Low Temperature Stability Impedance Ratio(MAX)	<table><tr><td>Rated Voltage (V)</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>Z(-40℃)/Z(20℃)</td><td>4</td><td>4</td><td>3</td><td>3</td></tr></table> (120Hz)					Rated Voltage (V)	16	25	35	50	Z(-40℃)/Z(20℃)	4	4	3	3		
Rated Voltage (V)	16	25	35	50													
Z(-40℃)/Z(20℃)	4	4	3	3													

◆DIMENSIONS

(mm)

φD	L	A1	B1	C	W1	P
6.3	6.1	6.6	6.6	2.7	0.5~0.8	1.8
6.3	8	6.6	6.6	2.7	0.5~0.8	1.8
8	10.5	8.3	8.3	2.9	0.8~1.1	3.1
10	10.5	10.3	10.3	3.2	0.8~1.1	4.5

◆MARKING

※ Voltage Code

Rated Voltage (V)	16	25	35	50
Rated Voltage code	C	E	V	H

※ Rated voltage code

Negative

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency (Hz)	120	1k	10k	100k≤
10~33μF	0.45	0.75	0.90	1.00
47~100μF	0.50	0.80	0.95	1.00
220~330μF	0.60	0.85	0.95	1.00

◆STANDARD SIZE

Size φD×L(mm), Ripple Current (mA r.m.s./125°C, 100kHz), ESR(Ω MAX/100kHz)

V.DC	Cap (μF)	Size (φD×L)	Ripple	ESR	
				20°C	-40°C
16 (1C)	33	6.3×6.1	70	1	15
	47	6.3×8	200	0.7	10
	100	6.3×8	200	0.7	10
		8×10.5	300	0.3	4.5
	220	8×10.5	300	0.3	4.5
		10×10.5	500	0.2	3
	330	10×10.5	500	0.2	3

V.DC	Cap (μF)	Size (φD×L)	Ripple	ESR	
				20°C	-40°C
25 (1E)	33	6.3×6.1	70	1	15
	47	6.3×8	200	0.7	10
	100	8×10.5	300	0.3	4.5
		8×10.5	300	0.3	4.5
	220	10×10.5	500	0.2	3
		10×10.5	500	0.2	3

V.DC	Cap (μF)	Size (φDxL)	Ripple	ESR	
				20℃	-40℃
35 (1V)	22	6.3×8	200	0.7	10
	33	6.3×6.1	70	1	15
		6.3×8	200	0.7	10
	47	6.3×8	200	0.7	10
		8×10.5	300	0.3	4.5
	100	8×10.5	300	0.3	4.5
		10×10.5	500	0.2	3
	220	10×10.5	500	0.2	3
50 (1H)	10	6.3×6.1	70	1	15
	22	6.3×8	150	0.9	10
	33	6.3×8	150	0.9	10
		8×10.5	250	0.36	4.5
	47	8×10.5	250	0.36	4.5
		10×10.5	350	0.25	3
	100	10×10.5	350	0.25	3

◆PART NUMBER

□□□	THV	□□□□□	M	□□□	D×L
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Case Size