

Low-Voltage 1:10 LVPECL/HSTL With Selectable Input Clock Driver

Check for Samples: [CDCLVP110](#)

FEATURES

- Distributes One Differential Clock Input Pair LVPECL/HSTL to 10 Differential LVPECL Clock Outputs
- Fully Compatible With LVECL/LVPECL/HSTL
- Single Supply Voltage Required, $\pm 3.3\text{-V}$ or $\pm 2.5\text{-V}$ Supply
- Selectable Clock Input Through CLK_SEL
- Low-Output Skew (Typ 15 ps) for Clock-Distribution Applications
- VBB Reference Voltage Output for Single-Ended Clocking
- Available in a 32-Pin LQFP Package
- Frequency Range From DC to 3.5 GHz
- Pin-to-Pin Compatible With MC100 Series EP111, ES6111, LVEP111, PTN1111


DESCRIPTION

The CDCLVP110 clock driver distributes one differential clock pair of either LVPECL or HSTL (selectable) input, (CLK0, CLK1) to ten pairs of differential LVPECL clock (Q0, Q9) outputs with minimum skew for clock distribution. The CDCLVP110 can accept two clock sources into an input multiplexer. The CLK0 input accepts either LVECL/LVPECL input signals, while CLK1 accepts an HSTL input signal when operated under LVPECL conditions. The CDCLVP110 is specifically designed for driving 50- Ω transmission lines.

The VBB reference voltage output is used if single-ended input operation is required. In this case the VBB pin should be connected to $\overline{\text{CLK0}}$ and bypassed to GND via a 10-nF capacitor.

However, for high-speed performance up to 3.5 GHz, the differential mode is strongly recommended.

The CDCLVP110 is characterized for operation from -40°C to 85°C .


Table 1. FUNCTION TABLE

| CLK_SEL | ACTIVE CLOCK INPUT |
|---------|--------------------------------|
| 0 | CLK0, $\overline{\text{CLK0}}$ |
| 1 | CLK1, $\overline{\text{CLK1}}$ |




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

CDCLVP110

SCAS683D – JUNE 2002 – REVISED JANUARY 2011

www.ti.com


These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.



TERMINAL FUNCTIONS

| TERMINAL | | DESCRIPTION |
|--------------------------------|--|--|
| NAME | NO. | |
| CLK_SEL | 2 | Clock select. Used to select between CLK0 and CLK1 input pairs. |
| CLK0, $\overline{\text{CLK0}}$ | 3, 4 | Differential LVECL/LVPECL input pair |
| CLK1, $\overline{\text{CLK1}}$ | 6, 7 | Differential HSTL input pair |
| Q [9:0] | 11, 13, 15, 18, 20, 22, 24, 27, 29, 31 | LVECL/LVPECL clock outputs, these outputs provide low-skew copies of CLKn. |
| $\overline{\text{Q}}$ [9:0] | 10, 12, 14, 17, 19, 21, 23, 26, 28, 30 | LVECL/LVPECL complementary clock outputs, these outputs provide copies of $\overline{\text{CLKn}}$. |
| V _{BB} | 5 | Reference voltage output for single-ended input operation |
| V _{CC} | 1, 9, 16, 25, 32 | Supply voltage |
| V _{EE} | 8 | Device ground or negative supply voltage in ECL mode |

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

| | | VALUE | UNIT |
|------------------|---------------------------|-------------------------------|------|
| V _{CC} | Supply voltage | –0.3 to 4.6 | V |
| V _I | Input voltage | –0.3 to V _{CC} + 0.5 | V |
| V _O | Output voltage | –0.3 to V _{CC} + 0.5 | V |
| I _{IN} | Input current | ±20 | mA |
| V _{EE} | Negative supply voltage | –0.3 to 4.6 | V |
| I _{BB} | Sink/source current | –1 to 1 | mA |
| I _O | DC output current | –50 | mA |
| T _{stg} | Storage temperature range | –65 to 150 | °C |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING CONDITIONS

| | | MIN | NOM | MAX | UNIT |
|-------------------------------|---|-------|---------|-----|------|
| V _{CC} | Supply voltage (relative to V _{EE}) | 2.375 | 2.5/3.3 | 3.8 | V |
| T _A ⁽¹⁾ | Operating free-air temperature | –40 | | 85 | °C |

- (1) Operating junction temperature affects device lifetime. The continuous operation junction temperature is recommended to be at max 110°C. The device ac and dc parameters are specified up to 85°C ambient temperature. See the *PCB Layout Guidelines for CDCLVP110* application note, literature number SCAA057 for more details.

PACKAGE THERMAL IMPEDANCE

| | | TEST CONDITIONS | MIN | MAX | UNIT |
|-----------------|---|-----------------|-----|-----|------|
| Θ _{JA} | Thermal resistance junction to ambient ⁽¹⁾ | 0 LFM | | 74 | °C/W |
| | | 150 LFM | | 66 | °C/W |
| | | 250 LFM | | 64 | °C/W |
| | | 500 LFM | | 61 | °C/W |
| Θ _{JC} | Thermal resistance junction to case | | | 39 | °C/W |

- (1) According to JESD 51-7 standard.

LVECL DC ELECTRICAL CHARACTERISTICS

V_{supply}: V_{CC} = 0 V, V_{EE} = –2.375 V to –3.8 V

| PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT | | |
|-------------------|--|--|-------------------|----------------------------|-------|-------|---|
| I _{EE} | Supply internal current Absolute value of current | –40°C | 40 | 78 | mA | | |
| | | 25°C | 45 | 82 | | | |
| | | 85°C | 48 | 85 | | | |
| I _{CC} | Output and internal supply current All outputs terminated 50 Ω to V _{CC} – 2 V | –40°C | | 343 | mA | | |
| | | 25°C | | 370 | | | |
| | | 85°C | | 380 | | | |
| I _{IN} | Input current | –40°C, 25°C, 85°C | | 150 | μA | | |
| V _{BB} | Internally generated bias voltage | For V _{EE} = –3 to –3.8 V, I _{BB} = –0.2 mA | –40°C, 25°C, 85°C | –1.45 | –1.3 | –1.15 | V |
| | | V _{EE} = –2.375 to –2.75 V, I _{BB} = –0.2 mA | –40°C, 25°C, 85°C | –1.4 | –1.25 | –1.1 | |
| V _{IH} | High-level input voltage (CLK_SEL) | –40°C, 25°C, 85°C | –1.165 | –0.88 | V | | |
| V _{IL} | Low-level input voltage (CLK_SEL) | –40°C, 25°C, 85°C | –1.81 | –1.475 | V | | |
| V _{INPP} | Input amplitude (CLK0, $\overline{\text{CLK0}}$) | Difference of input 9 V _{IH} –V _{IL} , See Note ⁽¹⁾ | –40°C, 25°C, 85°C | 0.5 | 1.3 | V | |
| V _{CM} | Common-mode voltage (CLK0, $\overline{\text{CLK0}}$) | Cross point of input 9 average (V _{IH} , V _{IL}) | –40°C, 25°C, 85°C | V _{EE} + 0.975 | –0.3 | V | |
| V _{OH} | High-level output voltage | I _{OH} = –21 mA | –40°C | –1.26 | –0.9 | V | |
| | | 25°C | –1.2 | –0.9 | | | |
| | | 85°C | –1.15 | –0.9 | | | |

- (1) V_{INPP} minimum and maximum is required to maintain ac specifications, actual device function tolerates a minimum V_{INPP} of 100 mV.

CDCLVP110

SCAS683D – JUNE 2002 – REVISED JANUARY 2011

www.ti.com

LVECL DC ELECTRICAL CHARACTERISTICS (continued)

 $V_{supply}: V_{CC} = 0\text{ V}, V_{EE} = -2.375\text{ V to } -3.8\text{ V}$

| PARAMETER | | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|-----------|-----------------------------------|---|-------------------|-------|-----|-------|------|
| V_{OL} | Low-level output voltage | $I_{OL} = -5\text{ mA}$ | -40°C | -1.85 | | -1.5 | V |
| | | | 25°C | -1.85 | | -1.45 | |
| | | | 85°C | -1.85 | | -1.4 | |
| V_{OD} | Differential output voltage swing | Terminated with 50 Ω to $V_{CC} - 2\text{ V}$, See Figure 3 | -40°C, 25°C, 85°C | 600 | | | V |

LVPECL/HSTL DC ELECTRICAL CHARACTERISTICS

 $V_{supply}: V_{CC} = 2.375\text{ V to } 3.8\text{ V}, V_{EE} = 0\text{ V}$

| PARAMETER | | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|------------|---|---|-------------------|------------------|-----------------|------------------|---------------|
| I_{EE} | Supply internal current | Absolute value of current | -40°C | 40 | | 78 | mA |
| | | | 25°C | 45 | | 82 | |
| | | | 85°C | 48 | | 85 | |
| I_{CC} | Output and internal supply current | All outputs terminated 50 Ω to $V_{CC} - 2\text{ V}$ | -40°C | | | 343 | mA |
| | | | 25°C | | | 370 | |
| | | | 85°C | | | 380 | |
| I_{IN} | Input current | | -40°C, 25°C, 85°C | | | 150 | μA |
| V_{BB} | Internally generated bias voltage | $V_{EE} = -3\text{ to } -3.8\text{ V}, I_{BB} = -0.2\text{ mA}$ | -40°C, 25°C, 85°C | $V_{CC} - 1.45$ | $V_{CC} - 1.3$ | $V_{CC} - 1.15$ | V |
| | | $V_{EE} = -2.375\text{ to } -2.75\text{ V}, I_{BB} = -0.2\text{ mA}$ | -40°C, 25°C, 85°C | $V_{CC} - 1.4$ | $V_{CC} - 1.25$ | $V_{CC} - 1.1$ | |
| V_{IH} | High-level input voltage (CLK_SEL) | | -40°C, 25°C, 85°C | $V_{CC} - 1.165$ | | $V_{CC} - 0.88$ | V |
| V_{IL} | Low-level input voltage (CLK_SEL) | | -40°C, 25°C, 85°C | $V_{CC} - 1.81$ | | $V_{CC} - 1.475$ | V |
| V_{INPP} | Input amplitude (CLK0, CLK0) | Difference of input 9 $V_{IH} - V_{IL}$, see Note (1) | -40°C, 25°C, 85°C | 0.5 | | 1.3 | V |
| V_{IC} | Common-mode voltage (CLK0, CLK0) | Cross point of input 9 average (V_{IH}, V_{IL}) | -40°C, 25°C, 85°C | 0.975 | | $V_{CC} - 0.3$ | V |
| V_{ID} | Differential input voltage (CLK1, CLK1) | Difference of input $V_{IH} - V_{IL}$, See Note (1) | -40°C, 25°C, 85°C | 0.4 | | 1.9 | V |
| $V_{I(x)}$ | Input crossover voltage (CLK1, CLK1) | Cross point of input 9 average (V_{IH}, V_{IL}) | -40°C, 25°C, 85°C | 0.68 | | 0.9 | V |
| V_{OH} | High-level output voltage | $I_{OH} = -21\text{ mA}$ | -40°C | $V_{CC} - 1.26$ | | $V_{CC} - 0.9$ | V |
| | | | 25°C | $V_{CC} - 1.2$ | | $V_{CC} - 0.9$ | |
| | | | 85°C | $V_{CC} - 1.15$ | | $V_{CC} - 0.9$ | |
| V_{OL} | Low-level output voltage | $I_{OL} = -5\text{ mA}$ | -40°C | $V_{CC} - 1.85$ | | $V_{CC} - 1.5$ | V |
| | | | 25°C | $V_{CC} - 1.85$ | | $V_{CC} - 1.45$ | |
| | | | 85°C | $V_{CC} - 1.85$ | | $V_{CC} - 1.4$ | |
| V_{OD} | Differential output voltage swing | Terminated with 50 Ω to $V_{CC} - 2\text{ V}$, See Figure 4 | -40°C, 25°C, 85°C | 600 | | | mV |

(1) V_{INPP} minimum and maximum is required to maintain ac specifications, actual device function tolerates a minimum V_{INPP} of 100 mV.

AC ELECTRICAL CHARACTERISTICS


V_{supply}: V_{CC} = 2.375 V to 3.8 V, V_{EE} = 0 V or LVECL/LVPECL input V_{CC} = 0 V, V_{EE} = -2.375 V to -3.8 V

| PARAMETER | | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|--------------------------------|---|--|-------------------|-----|-----|------|------|
| t _{pd} | Differential propagation delay CLK0, CLK0 to all Q0, Q0... Q9, Q9 | Input condition: V _{CM} = 1 V, V _{PP} = 0.5 V | -40°C, 25°C, 85°C | 230 | | 350 | ps |
| t _{sk(pp)} | Part-to-part skew | See Note B and Figure 1 | -40°C, 25°C, 85°C | | | 70 | ps |
| t _{sk(o)} | Output-to-output skew | See Note A and Figure 1 | -40°C, 25°C, 85°C | | 15 | 30 | ps |
| t _(JITTER) | Cycle-to-cycle RMS jitter | | -40°C, 25°C, 85°C | | | < 1 | ps |
| f _(max) | Maximum frequency | Functional up to 3.5 GHz, timing specifications apply at 1 GHz, see Figure 3 | -40°C, 25°C, 85°C | | | 3500 | MHz |
| t _r /t _f | Output rise and fall time (20%, 80%) | | -40°C, 25°C, 85°C | 100 | | 200 | ps |

HSTL INPUT

V_{supply}: V_{CC} = 2.375 V to 3.8 V, V_{EE} = 0 V

| PARAMETER | | TEST CONDITIONS | | MIN | TYP | MAX | UNIT |
|--------------------------------|---|--|-------------------|-----|-----|------|------|
| t _{pd} | Differential propagation delay CLK0, CLK0 to all Q0, Q0... Q9, Q9 | Input condition: V _x = 0.68 V, V _{diff} = 0.4 V | -40°C, 25°C, 85°C | 290 | | 370 | ps |
| t _{sk(pp)} | Part-to-part skew | See Note B and Figure 1 | -40°C, 25°C, 85°C | | | 70 | ps |
| t _{sk(o)} | Output to output skew | See Note A and Figure 1 | -40°C, 25°C, 85°C | | 10 | 30 | ps |
| t _(JITTER) | Cycle-to-cycle RMS jitter | | -40°C, 25°C, 85°C | | | < 1 | ps |
| f _(max) | Maximum frequency | Functional up to 3.5 GHz, timing specifications apply at 1 GHz, See Figure 4 | -40°C, 25°C, 85°C | | | 3500 | MHz |
| t _r /t _f | Output rise and fall time (20%, 80%) | | -40°C, 25°C, 85°C | 100 | | 200 | ps |



- A. Output skew is calculated as the greater of: The difference between the fastest and the slowest t_{PLHn} ($n = 0, 1, \dots, 9$) or the difference between the fastest and the slowest t_{pHLn} ($n = 0, 1, \dots, 9$).
- B. Part-to-part skew, is calculated as the greater of: The difference between the fastest and the slowest t_{PLHn} ($n = 0, 1, \dots, 9$) across multiple devices or the difference between the fastest and the slowest t_{pHLn} ($n = 0, 1, \dots, 9$) across multiple devices.

Figure 1. Waveform for Calculating Both Output and Part-to-Part Skew




Figure 2. Typical Termination for Output Driver (See the Interfacing Between LVPECL, LVDS, and CML Application Note, Literature Number SCAA056)




Figure 3. LVPECL Input Using CLK0 Pair, VCM = 1 V, VIN_{diff} = 0.5 V




Figure 4. HSTL Input Using CLK1 Pair, VCM = 0.68 V, VIN_{diff} = 0.4 V

REVISION HISTORY

| Changes from Revision A (August 2002) to Revision B | Page |
|--|------|
| • Changed PACKAGE THERMAL IMPEDANCE max values | 3 |
| • Deleted I_{IN} test condition | 3 |
| • Deleted I_{IN} test condition | 4 |
| Changes from Revision B (January 2010) to Revision C | Page |
| • Changed LVECL DC spec for V_{BB} ($V_{EE} = -3$ to -3.8 V) from 3 rows to 1 row and added TYP value. | 3 |
| • Changed LVECL DC spec for V_{BB} ($V_{EE} = -2.375$ to -2.75 V); MIN value from -1.38 V to -1.4 V, MAX from -1.16 V to -1.1 V, and added TYP value of -1.25 V | 3 |
| • Changed LVECL/HSTL DC spec for V_{BB} ($V_{EE} = -3$ to -3.8 V) from 3 rows to 1 row and added TYP value. | 4 |
| • Changed LVECL/HSTL DC spec for V_{BB} ($V_{EE} = -2.375$ to -2.75 V); MIN value from $V_{CC} -1.38$ V to $V_{CC} -1.4$ V; MAX from $V_{CC} -1.16$ V to $V_{CC} -1.1$ V; and added TYP value of $V_{CC} -1.25$ V | 4 |
| Changes from Revision C (January 2011) to Revision D | Page |
| • Changed V_{CM} spec from $V_{EE}+1$ to $V_{EE}+0.975$ | 3 |
| • Changed V_{IC} spec from 1 to 0.975 | 4 |

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish | MSL Peak Temp (3) | Op Temp (°C) | Top-Side Markings (4) | Samples |
|------------------|---------------|--------------|--------------------|------|----------------|----------------------------|------------------|----------------------|--------------|--------------------------|-------------------------|
| CDCLVP110MVFR | ACTIVE | LQFP | VF | 32 | 1000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | CDCLVP110 | Samples |
| CDCLVP110MVFRG4 | ACTIVE | LQFP | VF | 32 | 1000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | CDCLVP110 | Samples |
| CDCLVP110VF | ACTIVE | LQFP | VF | 32 | 250 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | CDCLVP110 | Samples |
| CDCLVP110VFG4 | ACTIVE | LQFP | VF | 32 | 250 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | CDCLVP110 | Samples |
| CDCLVP110VFR | ACTIVE | LQFP | VF | 32 | 1000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | CDCLVP110 | Samples |
| CDCLVP110VFRG4 | ACTIVE | LQFP | VF | 32 | 1000 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-1-260C-UNLIM | -40 to 85 | CDCLVP110 | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.


Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) Multiple Top-Side Markings will be inside parentheses. Only one Top-Side Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Top-Side Marking for that device.


Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CDCLVP110MVFR | LQFP | VF | 32 | 1000 | 330.0 | 16.4 | 9.6 | 9.6 | 1.9 | 12.0 | 16.0 | Q1 |
| CDCLVP110VFR | LQFP | VF | 32 | 1000 | 330.0 | 16.4 | 9.6 | 9.6 | 1.9 | 12.0 | 16.0 | Q2 |


TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CDCLVP110MVFR | LQFP | VF | 32 | 1000 | 341.0 | 159.0 | 123.5 |
| CDCLVP110VFR | LQFP | VF | 32 | 1000 | 367.0 | 367.0 | 38.0 |

VF (S-PQFP-G32)

PLASTIC QUAD FLATPACK



NOTES: A. All linear dimensions are in millimeters.
 B. This drawing is subject to change without notice.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

| | |
|------------------------------|--|
| Audio | www.ti.com/audio |
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DLP® Products | www.dlp.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| OMAP Applications Processors | www.ti.com/omap |
| Wireless Connectivity | www.ti.com/wirelessconnectivity |

Applications

| | |
|-------------------------------|--|
| Automotive and Transportation | www.ti.com/automotive |
| Communications and Telecom | www.ti.com/communications |
| Computers and Peripherals | www.ti.com/computers |
| Consumer Electronics | www.ti.com/consumer-apps |
| Energy and Lighting | www.ti.com/energy |
| Industrial | www.ti.com/industrial |
| Medical | www.ti.com/medical |
| Security | www.ti.com/security |
| Space, Avionics and Defense | www.ti.com/space-avionics-defense |
| Video and Imaging | www.ti.com/video |

TI E2E Community

e2e.ti.com