

Foot element - UMK-FE - 2970031

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Foot element, for mounting on DIN rail NS 32 or DIN rail NS 35/7.5, can be inserted between base and side element



The illustration shows a combination of versions UMK SE 11,25, UMK BE 11,25,- 22,5, -45 and UMK-FE

Product Features

- The modules can be marked using the marking grooves in the lateral element as well as with the Phoenix Contact PMB module marker, which is snapped into a bore hole (4 mm Ø) in the PCB
- Fast assembly thanks to the plug-in module principle. The tight engagement of the individual elements ensures that they are securely connected.
- ☑ Due to the universal foot, the modules can be snapped onto standard EN DIN rails



Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 017918 087562
Weight per Piece (excluding packing)	6.18 GRM
Custom tariff number	85472000
Country of origin	Poland

Technical data

General

Housing material	Polyamide
Color	green

Technical data



Foot element - UMK-FE - 2970031

Technical data

Technical data

Inflammability class according to UL 94	V2

Classifications

eCl@ss

aCl@aa 4.0	27180401
eCl@ss 4.0	27 10040 1
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182701
eCl@ss 8.0	27182701

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC002779

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approvals submitted



Foot element - UMK-FE - 2970031


Approvals

Approval details

UL Recognized **51**

Drawings

Dimensioned drawing



Phoenix Contact 2014 © - all rights reserved http://www.phoenixcontact.com