


C3216X5R1E226M160AB (TDK item description : C3216X5R1E226MT****)

Applications  Commercial Grade

Feature  General (Up to 50V)

Series C3216 [EIA CC1206]




Size	
Length(L)	3.20mm +/-0.20mm
Width(W)	1.60mm +/-0.20mm
Thickness(T)	1.60mm +/-0.20mm
Terminal Width(B)	0.20mm Min.
Terminal Spacing(G)	1.00mm Min.
Recommended Land Pattern(PA)	2.10 to 2.50mm (Flow Soldering) 2.00 to 2.40mm (Reflow Soldering)
Recommended Land Pattern(PB)	1.10 to 1.30mm (Flow Soldering) 1.00 to 1.20mm (Reflow Soldering)
Recommended Land Pattern(PC)	1.00 to 1.30mm (Flow Soldering) 1.10 to 1.60mm (Reflow Soldering)
Recommended Slit Pattern(SD)	

Electrical Characteristics	
Capacitance	22uF +/-20%
Rated Voltage	25Vdc
Temperature Characteristic	X5R(+/-15%)
Dissipation Factor	10% Max.
Insulation Resistance	22MΩ Min.


Other	
Soldering Method	Reflow, Flow
AEC Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	2000Pcs Min.

C3216X5R1E226M160AB


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




C3216X5R1E226M160AB




C3216X5R1E226M160AB




C3216X5R1E226M160AB



C3216X5R1E226M160AB



C3216X5R1E226M160AB(DC Bias = 0V) C3216X5R1E226M160AB(DC Bias = 12.5V)



C3216X5R1E226M160AB(100kHz) C3216X5R1E226M160AB(500kHz)
C3216X5R1E226M160AB(1MHz)