



enabling technologies

[10 Gig Ethernet](#)
[Data Centers](#)
[Fiber System Deployment](#)
[Grounding System for Data Centers](#)
[Industrial Ethernet](#)
[Managing the Physical Layer](#)
[Network Security](#)
[Power Over Ethernet](#)

product information

[Products](#)
[Bill of Material](#)
[My Catalog](#)
[Part Search](#)
[Cross Reference](#)
[FAQ's](#)
[Download / Request Literature](#)
[Downloads](#)

resources to help you

[Evaluate Technologies](#)
[Design a Solution](#)
[How to Buy](#)
[Evaluate, Design & Install Products](#)
[Download Panduit Logo](#)
[White Papers](#)
[RoHS Compliance](#)

value added services

[Strategic Alliance Program](#)
[Consultants](#)
[Distributors](#)
[Installers](#)
[System Integrators](#)
[Warranties](#)

Product Information: Products

[USA](#) | [Terminal Loose Piece](#) | [Standard Disconnects](#) | [Female Disconnects](#) |

Right Angle Female Disconnect, Nylon Fully Insulated – Funnel Entry



- Insulation support
- Used in limited space applications

Part Number	DNFR18-250FIB-M
Product Family	Right Angle Female Disconnect, Nylon Fully Insulated – Funnel Entry
RoHS Compliant	Compliant
Part Description	Female Disconnect, right angle, nylon fully insulated, funnel entry, 22-18 AWG, .250 x .032 tab size.
Product Type	Disconnects
CSA Certified	Yes
UL Listed	Yes
Depth (In.)	.60
Height (In.)	.21
Length (In.)	.58
Width (In.)	.37
Max. Ins.	.178
Panduit Color Code	Red
Std. Pkg. UOM	PK
Tab Size (In.)	.250 x .032
Tool	CT-300-1
Wire Range	22-18 AWG
UOM	PC
Std. Pkg. Qty.	1000
Min. Order Qty	1000
BOM Qty. (# of Pkgs.)	

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

evaluate

[FAQs](#)

design a solution

[Part Drawings](#)

install & maintain

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.