HOME	ABOUT US	KEY INDUSTRIES SERVED	PRODUCTS & INFORMATION	NEWS & EVENTS	SALES & SUF	PPORT	LOGIN
Honeywell	Sensing and	I Control					
Search	Э	SS361RT (Home: Products: Sensors » Magn	etic Sensors » 1st Level Hall-Effect				contact
narrow your search		Sensors » SS300)				Customer Service	
Products Controls Monitoring and Lighting (286) Machine Safety (1727)		SS300 Series Bipolar Latch Hall-Effect Digital Position Sensor; SOT-23 package, tape and reel				Technical Support Global Sales & Service View Site Demo Site Comments?	
<ul> <li>Sensors (618)</li> </ul>							
<ul> <li>Switches (978</li> </ul>	,						
• Wireless (45)							meet dr. la
Technology							
<ul> <li>Control and Instrumentation (890)</li> <li>Electromechanical (9303)</li> <li>Magnetic (538)</li> <li>Platinum thin film (56)</li> <li>Thick Film (1372)</li> </ul>		Actual product appearance				IDEO - Dr. Larry oldstein explains	0
					OL	our newest and best technologies.	
		may vary.					
			Sales & Service <b>()</b> Distributor Inventory <b>()</b>			Meet Dr. Larry	
More							
							my lin
		Overview Specs Docume	ntation Application Notes				
new products		Overview Specs Docume	ntation Application Notes			Login to iCOM	Dentel
new products		·	ntation Application Notes			Login to Rep/AD F	
	Products	Product Specifications				0	
New Wireless I So farther. Work sr	marter. Explore new	Product Specifications Product Type	Hall-Effect Digital F	Position Sensor IC		Login to Rep/AD F	
New Wireless I Go farther. Work sr ossibilities. Just by	marter. Explore new y cutting the cord	Product Specifications	Hall-Effect Digital F Tape and reel	Position Sensor IC		Login to Rep/AD F	niversity
New Wireless I to farther. Work sr ossibilities. Just by	marter. Explore new y cutting the cord	Product Specifications Product Type	Hall-Effect Digital F	Position Sensor IC		Login to Rep/AD F	niversity
New Wireless I Go farther. Work sr ossibilities. Just by	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type	Hall-Effect Digital F Tape and reel		_	Login to Rep/AD F Login to Digital Un HONEYWELL INT	News Cen
New Wireless I So farther. Work sr ossibilities. Just b ind making the swi	marter. Explore new y cutting the cord itch.	<b>Product Specifications</b> Product Type Package Quantity/Type Package Type	Hall-Effect Digital F Tape and reel SOT-23		_	Login to Rep/AD F Login to Digital Ur HONEYWELL INT TRUSTABILITY®	News Cent RODUCES
New Wireless I to farther. Work sr ossibilities. Just b nd making the swi	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd		_	Login to Rep/AD F Login to Digital Un HONEYWELL INT	News Cen RODUCES NSC SERIES
New Wireless I To farther. Work sr ossibilities. Just b nd making the swi	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink		_	Login to Rep/AD F Login to Digital Un HONEYWELL INT TRUSTABILITY® UNCOMPENSATI	News Cen RODUCES NSC SERIES ED / DARD MOUN
New Wireless I to farther. Work sr ossibilities. Just b ind making the swi	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount	ic		Login to Rep/AD F Login to Digital Un HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED B PRESSURE SEN: HONEYWELL EX	News Cen RODUCES NSC SERIES ED / DARD MOUN SORS PANDS ITS
New Wireless I o farther. Work sr bossibilities. Just b ind making the swit	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type	Hall-Effect Digital Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch	ic ∙40 °F to 302 °F]		Login to Rep/AD F Login to Digital Un HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED B PRESSURE SEN: HONEYWELL STM PL/	News Cen RODUCES NSC SERIES ED / DARD MOUN SORS PANDS ITS ATFORM WIT
New Wireless I bo farther. Work sr oossibilities. Just b ind making the swi version of the swi version of the swi version of the switch version of the swi	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature	Hall-Effect Digital f Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [-	ic ∙40 °F to 302 °F]	_	Login to Rep/AD F Login to Digital Ur HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED B PRESSURE SEN: HONEYWELL EXI LIMITLESS™ PL/ THE LAUNCH OL GLOBALLY AVAII	News Cen RODUCES NSC SERIES ED / DARD MOUN SORS PANDS ITS ABLE
New Wireless I oo farther. Work sr oossibilities. Just b ind making the swi of the swi of the swi vireless Web Site Vireless Web Site VGLA and WPMM	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [-	ic ∙40 °F to 302 °F]	_	HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED BC PRESSURE SEN: HONEYWELL EX LIMITLESSTPLE EX LIMITLESSTPLE THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR RECEIVER	News Cen RODUCES NSC SERIES ED / DARD MOUN SORS PANDS ITS TFORM WIT ITS LABLE ELESS
New Wireless I bo farther. Work sr ossibilities. Just b nd making the swi version of the swi version of the swi version of the switcher version of the	marter. Explore new y cutting the cord tich.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max.	ic ∙40 °F to 302 °F]	_	HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNAMPLIFED BU PRESSURE SEN: HONEYWELL EXT LIMITLESTM PL/ THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR	News Cen RODUCES NSC SERIES ED / DARD MOUN SORS PANDS ITS ATFORM WIT ITS ABLE ELESS TENDS ITS
New Wireless I oo farther. Work sr oossibilities. Just by nd making the swi wireless Web Site VGLA and WPMM YR6000 <sup>TM</sup>	marter. Explore new y cutting the cord tich.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %)	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 µs max.	ic -40 °F to 302 °F] -40 °F to 302 °F]	_	HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNCOMPENSATI UNCOMPENSATI UNCOMPENSATI UNCOMPENSATI UNAMPLIFIED BC PRESSURE SEN: HONEYWELL EX INITLESSTM PLZ HONEYWELL EX TRUSTABILITY® HONEYWELL EX TRUSTABILITY® SENSOR PRODU	News Cen RODUCES NSC SERIES ED / JARD MOUN SORS PANDS ITS LABLE ELESS TENDS ITS PRESSURE ICT LINE WIT
New Wireless I of arther. Work sr oossibilities. Just b ind making the swit weight of the switch wireless Web Site VGLA and WPMM YR6000™ white papers Wireless Switch	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %)	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 µs max. 1.5 µs max.	tc -40 °F to 302 °F] -40 °F to 302 °F] nax.	_	Login to Rep/AD F Login to Digital Ur TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED B PRESSURE SEN: HONEYWELL SXT THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR RECEIVER HONEYWELL EX TRUSTABILITY® SENSOR PRODU	News Cen RODUCES NSC SERIES ED / JARD MOUN SORS PANDS ITS LABLE ELESS TENDS ITS PRESSURE ICT LINE WIT
New Wireless I oo farther. Work sr oossibilities. Just b nd making the swi wireless Web Site VGLA and WPMM YR6000TM white papers Wireless Switch Unlimited Bene	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %) Operate Point	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 µs max. 1.5 µs max. 12.0 mT [120 G] m	tc -40 °F to 302 °F] -40 °F to 302 °F] nax.	_	HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNCOMPENSATI UNCOMPENSATI UNCOMPENSATI UNCOMPENSATI UNAMPLIFIED BC PRESSURE SEN: HONEYWELL EX INITLESSTM PLZ HONEYWELL EX TRUSTABILITY® HONEYWELL EX TRUSTABILITY® SENSOR PRODU	News Cen RODUCES NSC SERIES ED / JARD MOUN SORS PANDS ITS LABLE ELESS TENDS ITS PRESSURE ICT LINE WIT
New Wireless I to farther. Work so sostibilities. Just b and making the swi of the solution of the swi of the solution of the switch (Fireless Web Site (GLA and WPMM YR6000™ white papers Wireless Switch Unlimited Bene Basic Switches	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %) Operate Point Release Point	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 µs max. 1.5 µs max. 12.0 mT [120 G] m -12.0 mT [-120 G]	tc -40 °F to 302 °F] -40 °F to 302 °F] nax.	_	Login to Rep/AD F Login to Digital Ur TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED B PRESSURE SEN: HONEYWELL SXT THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR RECEIVER HONEYWELL EX TRUSTABILITY® SENSOR PRODU	News Cen RODUCES NSC SERIE: ED / JARD MOUN SORS PANDS ITS LABLE ELESS TENDS ITS PRESSURE ICT LINE WIT
New Wireless I o farther. Work sp ossibilities. Just b nd making the swi of the swi of the swi of the swi of the swi of the switch of the switch of the switch of the switch of the switch of the swit	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %) Operate Point Release Point Availability Supply Current	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 µs max. 1.5 µs max. 12.0 mT [120 G] m -12.0 mT [-120 G] Global	tc -40 °F to 302 °F] -40 °F to 302 °F] nax.	_	HONEYWELL INT TRUSTABILITY® UNCOMPENSATI UNAMPLIFIED BC PRESSURE SEN: HONEYWELL EXILIMITLESS <sup>TM</sup> PLZ HONEYWELL EXILIMITLESS <sup>TM</sup> PLZ HONEYWELL EXILIMITAL WIR RECEIVER HONEYWELL EXI SENSOR PRODU A SINGLE SIDE L OPTION	News Cen RODUCES NSC SERIE: ED / JARD MOUN SORS PANDS ITS LABLE ELESS TENDS ITS PRESSURE ICT LINE WIT
New Wireless I o farther. Work sp ossibilities. Just b nd making the swi of the swi of the swi of the switch space sp of the switch space sp white papers Wireless Switch Dulimited Bene Basic Switches Equal Applying Precis	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %) Operate Point Release Point Availability Supply Current Output Current (max.)	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 µs max. 1.5 µs max. 12.0 mT [120 G] Global 8 mA	tc -40 °F to 302 °F] -40 °F to 302 °F] nax.	_	Login to Rep/AD F Login to Digital Un TRUSTABILITY® UNCOMPENSATT UNAMPLIFIED B PRESSURE SEN: HONEYWELL EX THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR RECEIVER HONEYWELL EX TRUSTABILITY® SENSOR PRODU SENSOR PRODU	News Cen RODUCES NSC SERIE: ED / JARD MOUN SORS PANDS ITS TFORM WIT ITS ABLE ELESS TENDS ITS PRESSURE (CL LINE WI IQUID MEDI
New Wireless I o farther. Work sp ossibilities. Just b ind making the swi of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switch of the switc	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %) Operate Point Release Point Availability Supply Current Output Current (max.) Leakage Current	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 μs max. 1.5 μs max. 12.0 mT [120 G] m -12.0 mT [-120 G] Global 8 mA 20 mA 10 μA max.	40 °F to 302 °F] 40 °F to 302 °F] 40 °F to 302 °F] nax. min. @ 25 °C	_	Login to Rep/AD F Login to Digital Un TRUSTABILITY® UNCOMPENSATT UNAMPLIFIED B PRESSURE SEN: HONEYWELL EX THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR RECEIVER HONEYWELL EX TRUSTABILITY® SENSOR PRODU SENSOR PRODU	News Cen RODUCES NSC SERIE: ED / DARD MOUN SORS PANDS ITS ABLE ELESS TENDS ITS PRESSURE TENDS ITS PRESSURE CT LINE WI IQUID MEDI
New Wireless I o farther. Work sp ossibilities. Just b nd making the swi of the swi of the swi of the switch space sp of the switch space sp white papers Wireless Switch Dulimited Bene Basic Switches Equal Applying Precis	marter. Explore new y cutting the cord itch.	Product Specifications Product Type Package Quantity/Type Package Type Supply Voltage Output Type Termination Type Magnetic Actuation Type Operating Temperature Storage Temperature Output Voltage Switching Time Rise (10 % to 90 %) Switching Time Fall (90 % to 10 %) Operate Point Release Point Availability Supply Current Output Current (max.)	Hall-Effect Digital F Tape and reel SOT-23 3.0 Vdc to 12.0 Vd Sink Surface Mount Bipolar Latch -40 °C to 150 °C [- -40 °C to 150 °C [- 0.4 Vdc max. 1.5 μs max. 1.5 μs max. 1.5 μs max. 1.2.0 mT [120 G] Global 8 mA 20 mA	40 °F to 302 °F] 40 °F to 302 °F] 40 °F to 302 °F] nax. min. @ 25 °C	_	Login to Rep/AD F Login to Digital Un TRUSTABILITY® UNCOMPENSATT UNAMPLIFIED B PRESSURE SEN: HONEYWELL EX THE LAUNCH OF GLOBALLY AVAII INDUSTRIAL WIR RECEIVER HONEYWELL EX TRUSTABILITY® SENSOR PRODU SENSOR PRODU	News Cen RODUCES NSC SERIE: ED / JARD MOUN SORS PANDS ITS TFORM WIT ITS ABLE ELESS TENDS ITS PRESSURE (CL LINE WI IQUID MEDI

## Need help?

Click here to contact us

Terms & Conditions | Privacy Statement | Site Map