

## Power supply unit - STEP-PS-100-240AC/15DC/2.4 - 2938934

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

DIN rail power supply unit 15 V DC/2.4 A, primary-switched mode, low-profile design



### Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	264.1 GRM
Custom tariff number	85044094
Country of origin	China

### Technical data

#### Dimensions

Width	71 mm
Height	90 mm
Depth	55 mm

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	95 % (at 25 °C, no condensation)

#### Input data

Nominal input voltage range	100 V AC ... 240 V AC
Input voltage range AC	85 V AC ... 264 V AC
AC frequency range	45 Hz ... 65 Hz
Frequency range DC	0 Hz
Current consumption	0.8 A (120 V AC)

## Power supply unit - STEP-PS-100-240AC/15DC/2.4 - 2938934

### Technical data

#### Input data

	0.4 A (230 V AC)
Nominal power consumption	36 W
Inrush surge current	< 25 A (typical)
Power failure bypass	> 20 ms (120 V AC)
	> 100 ms (230 V AC)
Input fuse	1.25 A (Normal blow, internal)

#### Output data

Nominal output voltage	15 V DC $\pm 1\%$
Output current	2.4 A (up to 55°C)
	approx. 7 A (maximum output current $I_{max}$ )
Connection in parallel	Yes, for redundancy and increased capacity
Connection in series	No
Control deviation	< 1 % (change in load, static 10% ... 90%)
	< 3 % (change in load, dynamic 10% ... 90%)
	< 0.1 % (change in input voltage $\pm 10\%$ )
Residual ripple	< 40 mV <sub>PP</sub>
Peak switching voltages nominal load	< 50 mV <sub>PP</sub> (20 MHz)
Maximum power dissipation NO-Load	< 2 W
Power loss nominal load max.	< 8 W

#### General

Net weight	0.2 kg
Efficiency	> 80 %
Insulation voltage input/output	3 kV (routine test)
	4 kV (type test)
MTBF (IEC 61709, SN 29500)	> 500000 h
Mounting position	horizontal DIN rail NS 35, EN 60715
Assembly instructions	Alignable: 0 mm horizontally, 30 mm vertically
Electromagnetic compatibility	Conformance with EMC directive 89/336/EC
Standard - Safety of transformers	EN 61558-2-17
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
	EN 61558-2-17
	EN 50178 (PELV)
Standard - Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
Standard - Safe isolation	DIN VDE 0100-410
	DIN VDE 0106-1010

# Power supply unit - STEP-PS-100-240AC/15DC/2.4 - 2938934

## Technical data

### General

Standard – Limitation of mains harmonic currents	EN 61000-3-2
UL approvals	UL/C-UL listed UL 508
	UL/C-UL Recognized UL 60950
Surge voltage category	III

### Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Stripping length	6.5 mm
Screw thread	M3

### Connection data, output

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	14
Stripping length	6.5 mm

### Signaling

Output name	POWER
Status display	Green LED
Output name	OVERLOAD
Status display	LED red

## Classifications

### eCl@ss

eCl@ss 4.0	27250202
eCl@ss 4.1	27250202
eCl@ss 5.0	27143114
eCl@ss 5.1	27143114

# Power supply unit - STEP-PS-100-240AC/15DC/2.4 - 2938934

## Classifications

eCl@ss

eCl@ss 6.0	27143114
------------	----------

## ETIM

ETIM 2.0	EC001039
ETIM 3.0	EC001039
ETIM 4.0	EC000599

## UNSPSC

UNSPSC 6.01	30211502
UNSPSC 7.0901	39121004
UNSPSC 11	39121004
UNSPSC 12.01	39121004
UNSPSC 13.2	39121004

## Drawings

Block diagram

