



### enabling technologies

[10 Gig Ethernet](#)  
[Data Centers](#)  
[Fiber System Deployment](#)  
[Grounding System for Data Centers](#)  
[Industrial Ethernet](#)  
[Managing the Physical Layer](#)  
[Network Security](#)  
[Power Over Ethernet](#)

### product information

[Products](#)  
[Bill of Material](#)  
[My Catalog](#)  
[Part Search](#)  
[Cross Reference](#)  
[FAQ's](#)  
[Download / Request Literature](#)  
[Downloads](#)

### resources to help you

[Evaluate Technologies](#)  
[Design a Solution](#)  
[How to Buy](#)  
[Evaluate, Design & Install Products](#)  
[Download Panduit Logo](#)  
[White Papers](#)  
[RoHS Compliance](#)

### value added services

[Strategic Alliance Program](#)  
[Consultants](#)  
[Distributors](#)  
[Installers](#)  
[System Integrators](#)  
[Warranties](#)

### Product Information: Products

[USA](#) | [Heat Shrink & Abrasion Protection](#) | [Heat Shrink](#) | [General Purpose, Flexible Polyolefin for Dry Locations](#) |  
**HSTT Heat Shrink 4 ft (1.2M) Pieces**



### evaluate

[FAQs](#)

### design a solution

### install & maintain

- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance

For clear, add "C" to end of part number package suffix (Example HSTT05-48-QC). Contact customer service for additional color information.

^ Meets Mil Spec AMS-DTL-23053/5 Class 1.

Part Number	HSTT19-48-Q
Product Family	HSTT Heat Shrink 4 ft (1.2M) Pieces
RoHS Compliant	Compliant
Part Description	Thin Wall Polyolefin Heat Shrink
Material	Flame retardant polyolefin cross-linked except clear <sup>^</sup>
Color	Black <sup>‡</sup>
CSA Certified	Yes
Military Specification	AMS-DTL-23053/5 Class 1
UL Recognized	E122770
Length (Ft.)	4
Flammability Rating	Flame Retardant
Max. Recovered I.D. (In.)	.093
Max. Recovered I.D. (mm)	2.4
Min. Expanded I.D. (In.)	.187
Min. Expanded I.D. (mm)	4.8
Nominal Diameter / Size	3/16
Nominal Recovered Wall Thickness (In.)	.020
Nominal Recovered Wall Thickness (mm)	.5
Shrink Ratio	2:1
Std. Pkg. UOM	PK
Temperature Range	-67°F to 275°F (-55°C to 135°C)
UOM	PC

Std. Pkg. Qty.	25
Min. Order Qty	25
BOM Qty. (# of Pkgs.)	

Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2005, PANDUIT CORP. All rights reserved.