

Sta-Kon®

Terminals

Locking fork terminals have a specially designed tongue that lets them go on like a fork and stay on like a ring.



Stock thickness same as ring terminal of same size.


Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Nylon Insulated Locking Fork – Insulation Grip

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
RA18-6FL	100	22-16	.136	#6	5	.86	.25	.25	.71
RA2213	1000	22-16	.136	#6	5	.86	.25	.25	.71
RA18-8FL	100	22-16	.136	#8	5	.86	.29	.25	.71
RA2243	1000	22-16	.136	#8	5	.86	.29	.25	.71
RA18-10FL	100	22-16	.136	#10	5	.86	.29	.25	.71
RA2253	1000	22-16	.136	#10	5	.86	.29	.25	.71
RB14-6FL	100	18-14	.162	#6	6	.87	.25	.25	.71
RB2213	1000	18-14	.162	#6	6	.87	.25	.25	.71
RB2214	1000	18-14	.190	#6	6	.95	.25	.25	.79
RB14-8FL	100	18-14	.162	#8	6	.87	.29	.25	.71
RB2233	1000	18-14	.162	#8	6	.87	.29	.25	.71
RB14-10FL	100	18-14	.162	#10	6	.87	.29	.25	.71
RB2253	1000	18-14	.162	#10	6	.87	.29	.25	.71
RB2254	1000	18-14	.190	#10	6	.95	.29	.25	.71
RC10-6FL	50	12-10	.210	#6	8	.97	.31	.27	.81
RC2203	500	12-10	.210	#6	8	.97	.31	.27	.81
RC2204	1000	12-10	.250	#6	8	1.07	.31	.27	.91
RC10-8FL	50	12-10	.210	#8	8	1.00	.37	.27	.81
RC2213	500	12-10	.210	#8	8	1.00	.37	.27	.81
RC10-10FL	50	12-10	.210	#10	8	1.00	.37	.27	.81
RC2223	500	12-10	.210	#10	8	1.00	.37	.27	.81
RC2224	1000	12-10	.250	#10		1.10	.37	.27	.91
RC10-14FL	50	12-10	.210	1/4"	8	1.12	.50	.32	.86
RC2233	500	12-10	.210	1/4"	8	1.12	.50	.32	.86

U.L. Listed E9809

Installing tools: ERG4001, ERG2003, WT145C, WT2000, WT112M, WT145A, WT2130A(RC)






Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Vinyl Insulated Locking Fork – Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
18RA-6FL	100	22-16	.150	#6	5	.97	.25	.25	.81
RA2217	1000	22-16	.150	#6	5	.97	.25	.25	.81
RA2227	1000	22-16	.155	#6	5	.97	.29	–	.81
18RA-8FL	100	22-16	.150	#8	5	.97	.29	.25	.81
RA2247	1000	22-16	.150	#8	5	.97	.29	.25	.81
18RA-10FL	100	22-16	.150	#10	5	.97	.29	.25	.81
RA2257	1000	22-16	.150	#10	5	.97	.29	.25	.81
14RB-6FL	100	18-14	.170	#6	6	.97	.25	.27	.81
RB2207	1000	18-14	.170	#6	6	.97	.25	.27	.81
RB2217	1000	18-14	.170	#6	6	.97	.29	.27	.81
14RB-8FL	100	18-14	.170	#8	6	.97	.29	.27	.81
RB2237	1000	18-14	.170	#8	6	.97	.29	.27	.81
14RB-10FL	100	18-14	.170	#10	6	.97	.29	.27	.81
RB2257	1000	18-14	.170	#10	6	.97	.29	.27	.81
10RC-6FL	50	12-10	.220	#6	8	1.09	.31	.27	.90
RC2207	500	12-10	.220	#6	8	1.09	.31	.27	.90
10RC-8FL	50	12-10	.220	#8	8	1.09	.37	.27	.90
RC2217	500	12-10	.220	#8	8	1.09	.37	.27	.90
10RC-10FL	50	12-10	.220	#10	8	1.09	.37	.27	.90
RC2227	500	12-10	.220	#10	8	1.09	.37	.27	.90
10RC-14FL	50	12-10	.220	1/4"	8	1.09	.49	.27	.90
RC2237	500	12-10	.220	1/4"	8	1.09	.49	.27	.90

U.L. Listed E9809. Installing tools: ERG4001, ERG2003, WT145C, WT2000, WT112M




Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Vinyl Insulated Locking Fork – Expanded Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
18RA-6FLX	100	22-16	.170	#6	5	.97	.25	.25	.81
18RA-8FLX	100	22-16	.170	#8	5	.97	.29	.25	.81
18RA-10FLX	100	22-16	.170	#10	5	.97	.29	.25	.81
RA2257-170	1000	22-16	.170	#10	5	.97	.29	.25	.81
14RB-6FLX	100	18-14	.200	#6	6	.97	.31	.27	.81
RB2207-200	1000	18-14	.200	#6	6	.97	.31	.27	.81
RB2217-200	1000	18-14	.200	#6	6	.97	.29	.27	.81
14RB-8FLX	100	18-14	.200	#8	6	.97	.31	.27	.81
RB2237-200	1000	18-14	.200	#8	6	.97	.31	.27	.81
14RB-10FLX	100	18-14	.200	#10	6	.97	.31	.27	.81
RB2257-200	1000	18-14	.200	#10	6	.97	.31	.27	.81
10RC-6FLX	50	12-10	.250	#6	8	1.07	.31	.27	.91
RC2207-250	500	12-10	.250	#6	8	1.07	.31	.27	.91
10RC-8FLX	50	12-10	.250	#8	8	1.10	.37	.27	.91
10RC-10FLX	50	12-10	.250	#10	8	1.10	.37	.27	.91
RC2227-250	500	12-10	.250	#10	8	1.10	.37	.27	.91
10RC-14FLX	50	12-10	.250	1/4"	8	1.22	.50	.32	.96

U.L. Listed E9809. Installing tools: ERG4001, ERG2003, WT145C, WT2000, WT112M






Heat Shrinkable Locking Fork Terminals – Expanded Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions	
						A	B
RAS18-6FLX	100	22-18	.170	#6	5	1.350	.25
RAS18-8FLX	100	22-18	.170	#8	5	1.350	.29
RAS18-10FLX	100	22-18	.170	#10	5	1.350	.29
RBS14-6FLX	100	16-14	.200	#6	6	1.350	.25
RBS14-8FLX	100	16-14	.200	#8	6	1.350	.29
RBS14-10FLX	100	16-14	.200	#10	6	1.350	.29
RCS10-6FLX	50	12-10	.250	#6	8	1.350	.31
RCS10-8FLX	50	12-10	.250	#8	8	1.350	.37
RCS10-10FLX	50	12-10	.250	#10	8	1.350	.37
RCS10-14FLX	50	12-10	.250	1/4"	8	1.350	.49

U.L. Listed E9809

Installing tool: WT1255

Note: Heat Shrinkable terminals not available on Mylar Tape.




Non-Insulated Locking Fork

Cat. No.	Pkg. Qty.	Wire Range	Bolt Hole	Wt./lb. Per 1000	Dimensions			
					A	B	C	M
A18-6FL	100	22-16	#6	4-3/4	.75	.25	.27	.59
A221	1000	22-16	#6	4-3/4	.75	.25	.27	.59
A18-8FL	100	22-16	#8	4-3/4	.75	.29	.27	.59
A224	1000	22-16	#8	4-3/4	.75	.29	.27	.59
A18-10FL	100	22-16	#10	4-3/4	.75	.29	.27	.59
A225	1000	22-16	#10	4-3/4	.75	.29	.27	.59
B14-6FL	100	18-14	#6	4-3/4	.75	.25	.27	.59
B220	1000	18-14	#6	4-3/4	.75	.25	.27	.59
B14-8FL	100	18-14	#8	4-3/4	.75	.29	.27	.59
B223	1000	18-14	#8	4-3/4	.75	.29	.27	.59
B14-10FL	100	18-14	#10	4-3/4	.75	.29	.27	.59
B225	1000	18-14	#10	4-3/4	.75	.29	.27	.59
C10-6FL	50	12-10	#6	4-3/4	.85	.31	.27	.66
C220-TB	500	12-10	#6	4-3/4	.85	.31	.27	.66
C10-8FL	50	12-10	#8	4-3/4	.85	.37	.27	.66
C221	500	12-10	#8	4-3/4	.85	.37	.27	.66
C10-10FL	50	12-10	#10	4-3/4	.85	.37	.27	.66
C222-TB	500	12-10	#10	4-3/4	.85	.37	.27	.66
C10-14FL	50	12-10	1/4"	4-3/4	.85	.49	.27	.66

U.L. Listed E9809

Installing tools: WT110M, WT111M, WT112M, WT2000, ERG4002, ERG4005



Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)