

## SMD030F-2 Product Details



**SMD030F-2**

TE Internal Number: RF0314-000

 **Active**

### PolySwitch Resettable Devices

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)


#### Product Highlights:

- Surface Mount Application
- Family Name = SMD
- Surface Mount Construction
- IH (Room Temperature) = 1.1 Amps.
- IT (Room Temperature) = .60 Amps.

[View all Features](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#)
 [Request Sample](#)
 [Find Similar Products](#)
 [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- UL Recognized = E74889
- CSA File No. = CA78165

#### Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 1.1
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.60
- [Vmax Operating \(V\)](#) = 60
- [Rmin \(Ω\)](#) = 1.20
- [R1 Max \[Post Trip\] \(Ω\)](#) = 4.80
- Vmax (V) = 60
- Imax (Amps.) = 10
- Power Dissipation (Max) (W) = 1.7

#### Termination Related Features:

- Construction = Surface Mount

#### Contact Related Features:

- [Family Name](#) = SMD

#### Configuration Related Features:

- [Form Factor \(inches\)](#) = 2920
- [Form Factor \(mm\)](#) = 7555

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041427

#### Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

#### Operation/Application:

- Application = Surface Mount

#### Packaging Related Features:

- Packaging Method = Tape & Reel

#### Other:

- Brand = Raychem

 [BOOKMARK](#) 

### Corporate Information

[Who We Are](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)

### Quick Links

[Check Distributor Inventory](#)  
[Cross Reference](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

### Customer Support

[Email or Chat with Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage Your Account](#)