

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
AD	00	D1	REVISED PER ECO-11-004587		11MAR11	RK	HMR

44 POS.

52 POS.

68 POS.

84 POS.

RECOMMENDED HOLE LAYOUT  
 TOLERANCE:  $\pm 0.05$  [.002] UNLESS OTHERWISE NOTED

NOTES:

1

MATERIALS:

CONTACT: COPPER ALLOY, 0.004572 [.000180] MIN TIN PLATE  
 OVER 0.00127 [.000050] MIN NICKEL.  
 INSULATOR: PPS, 40% GLASS FILLED, UL 94V-0

2

DATE CODE (PER BELOW) TO BE LASER CODED  
 AND CENTERED ON THIS SURFACE.

3. UL RECOGNITION E320916.

SEE NOTE 2  
 PIN 1, INDENTIFIERS  
 $\phi 0.89$  [ $\phi 0.035$ ] THRU PIN 1  
 2.54 [.100] TYP.  
 $\phi 1.58$  [ $\phi 0.062$ ] SOLDER PAD

"A" MAX. SQ.  
 "B" SQ.  
 1.65 [.065]  
 9.14 [.360]  
 3.30 [.130]  
 2.54 [.100]  
 "C" SQ.  
 "D" SQ.  
 1.09 [.043]  
 0.51 [.020]  
 0.25 [.010]

PART NO.	POS.	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"
1571541-1	44	22.61 [.890]	16.76 [.660]	12.70 [.500]	17.78 [.700]
1571541-2	52	25.15 [.990]	19.30 [.760]	15.24 [.600]	20.32 [.800]
1571541-3	68	30.23 [1.190]	24.38 [.960]	20.32 [.800]	25.40 [1.000]
1571541-4	84	35.31 [1.390]	29.46 [1.160]	25.40 [1.000]	30.48 [1.200]

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D. MURREN 26AUG2003	TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK K. WRIGHT 24APR03	OBSOLETE	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K. WRIGHT 24APR03	OUTLINE DRAWING	
0 PLC $\pm$ -		PRODUCT SPEC	PLCC SOCKET	
1 PLC $\pm$ 1		108-38000	NOT the LATEST REVISION	
2 PLC $\pm$ 0.25 [.010]		APPLICATION SPEC	RESTRICTED TO	
3 PLC $\pm$ -		SIZE CAGE CODE DRAWING NO	A2 00779 C=1571541	
4 PLC $\pm$ -		WEIGHT	SCALE 2:1 SHEET 1 OF 1 REV D1	
ANGLES $\pm$ 1°		CUSTOMER DRAWING		
FINISH 1				

1471-9 (3/11)

1571541

B

A