


600H & 600NH SERIES - POWER TOGGLE SWITCHES

A



FEATURES

- Motor load and power ratings.
- Single, double & three pole models with nickel plated brass or insulated actuators.
- Locking actuator options for single & double poles.

SPECIFICATIONS

Contact ratings (resistive loads):	Functions ON-OFF and ON-ON: 15A 250VAC or 10A 24VDC Functions ON OFF ON: 15A 250VAC Other functions: 12A 250VAC, 15A 125VAC or 5A 25VDC
Maximum approved ratings:	UL/CSA: SP, DP & 3P functions ON-ON & 3P function ON-OFF - 15A 1/2HP 125/250 VAC. Other functions 10A 1/2HP 125/250VAC VDE: 600NH SP & DP function ON-ON only - 10(4)A 400VAC, grounding lug ring, p/n U187 required (order separately).
Initial contact resistance:	10 milliohms maximum
Insulation resistance:	1000 megohms min. at 500 VDC
Dielectric strength:	2000 V rms min. - between terminals 2500 V rms min. - between terminals and frame
Electrical life at full load:	10,000 cycles minimum
Operating temperature range:	-20°C to +55°C

MATERIALS

Contacts:	Silver/nickel alloy
Actuator:	600H: nickel plated brass 600NH: black polyamide
Bushing:	Nickel plated brass
Housing:	Stainless steel or tin plated steel
Case:	Melamine/polyester
Hardware:	600H models are supplied with 1 Hex Nut p/n U166 & 1 Knurled Nut p/n U411. 600NH models are supplied with 1 Hex Nut U166 & 1 black Knurled Nut p/n U522. See hardware section of catalog.

AGENCY RECOGNITION



UL & CSA: 600H.

VDE, UL & CSA: 600NH. Recognition markings are standard.

ABOUT THIS SERIES

The material in this series is organized in the following sequence:

- Completely specified switch models
- 'build your own switch' order format
- Option drawings & special options
- Miscellaneous

ALSO IN THIS SERIES

Switches for peak currents - for switching power supplies, DC-DC converters, motors, etc. See specifications on last page of completely specified models.


SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

600H & 600NH SERIES - POWER TOGGLE SWITCHES

Single pole - nickel plated brass actuator



SOLDER LUG	SCREW TERMS.	CIRCUIT
631H/2	631H	ON - OFF
635H/2	635H	MOM - ON
636H/2	636H	ON - ON
637H/2	637H	MOM OFF MOM
638H/2	638H	ON OFF MOM
639H/2	639H	ON OFF ON
Handle position (see dwg.):		III II I
Terminals connected:		2-1 2-3




→ Keyway

Double pole - nickel plated brass actuator



SOLDER LUG	SCREW TERMS.	CIRCUIT
641H/2	641H	ON - OFF
644H/2*	644H*	ON ON ON
644H/21R*	644H1R*	ON ON MOM
644H/22R*	644H2R*	MOM ON MOM
645H/2	645H	MOM - ON
646H/2	646H	ON - ON
647H/2	647H	MOM OFF MOM
648H/2	648H	ON OFF MOM
649H/2	649H	ON OFF ON
Handle position:		III II I
Terminals connected:		2-1 2-3 5-4 5-6




→ Keyway

* Function 4: SP in DP case. See info. at end of section.

Three pole - nickel plated brass actuator



SOLDER LUG	SCREW TERMS.	CIRCUIT
651H/2	651H	ON - OFF
655H/2	655H	MOM - ON
656H/2	656H	ON - ON
657H/2	657H	MOM OFF MOM
658H/2	658H	ON OFF MOM
659H/2	659H	ON OFF ON
Handle position:		III II I
Terminals connected:		2-1 2-3 5-4 5-6 8-7 8-9




→ Keyway

Single pole - insulated actuator



SOLDER LUG	SCREW TERMS.	CIRCUIT
631NH/2	631NH	ON - OFF
635NH/2	635NH	MOM - ON
636NH/2	636NH	ON - ON
637NH/2	637NH	MOM OFF MOM
638NH/2	638NH	ON OFF MOM
639NH/2	639NH	ON OFF ON
Handle position (see dwg.):		III II I
Terminals connected:		2-1 2-3



→ Keyway

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

600H & 600NH SERIES - POWER TOGGLE SWITCHES


A

Double pole - insulated actuator



SOLDER LUG	SCREW TERMS.	CIRCUIT		
641NH/2	641NH	ON	-	OFF
644NH/2*	644NH*	ON	ON	ON
644NH/21R*	644NH1R*	ON	ON	MOM
644NH/22R*	644NH2R*	MOM	ON	MOM
645NH/2	645NH	MOM	-	ON
646NH/2	646NH	ON	-	ON
647NH/2	647NH	MOM	OFF	MOM
648NH/2	648NH	ON	OFF	MOM
649NH/2	649NH	ON	OFF	ON
Handle position:		III	II	I
Terminals connected:		2-1	2-3	5-6

* Function 4: SP in DP case. See info. at end of section.




→ Keyway

Three pole - insulated actuator



SOLDER LUG	SCREW TERMS.	CIRCUIT		
651NH/2	651NH	ON	-	OFF
655NH/2	655NH	MOM	-	ON
656NH/2	656NH	ON	-	ON
657NH/2	657NH	MOM	OFF	MOM
658NH/2	658NH	ON	OFF	MOM
659NH/2	659NH	ON	OFF	ON
Handle position:		III	II	I
Terminals connected:		2-1	2-3	5-6
		5-4	5-6	8-9



→ Keyway

600SH & 600SNH - switches for peak currents - up to 150 Amps at 250 VAC

Contacts:

Silver cadmium oxide

Capacitive load ratings:

15/150A 125VAC & 250VAC - 5,000 cycles
 10/150A 125VAC & 250VAC - 10,000 cycles
 4/90A (10ms) 60VDC - 10,000 cycles

Motor load ratings:

(note: 15(6)A 250VAC= 15A resistive and 6A motor)
 15(6)A 250VAC - 10,000 cycles 10(4)A 380VAC - 10,000 cycles
 17(6)A 125VAC - 6,000 cycles 1 HP 250VAC - 10,000 cycles
 2 HP 250VAC - 6,000 cycles 1/2 HP 125VAC - 6,000 cycles

Lamp load ratings:

10A 125VAC & 250VAC - 10,000 cycles

Other specs. & dimensions:

Same as 600H & 600NH models previously described.
 Compatible with options **T, G, K, 1V, 2V & 3V.**



Single and double pole models are UL approved (3/4 HP 125VAC)
 Also see 'Switches for Peak Currents' technical page in rear of catalog.

SCREW TERMINALS WITH CLAMP	SOLDER LUG QUICK-CONNECT TERMINALS	CIRCUIT
SINGLE POLE		
631SH	631SH/2	ON - OFF
636SH	636SH/2	ON - ON
DOUBLE POLE		
641SH	641SH/2	ON - OFF
646SH	646SH/2	ON - ON
THREE POLE		
651SH	651SH/2	ON - OFF
656SH	656SH/2	ON - ON

Above models have nickel plated brass actuator. For insulated actuator, replace 'SH' in above model numbers with 'SNH'.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

600H & 600NH SERIES - POWER TOGGLE SWITCHES

Additional ordering information: Commonly ordered models are shown on prior pages with complete model numbers and specifications. Below is an order format that enables you to 'build your own switch' and specify the correct switch model number by simply selecting from all available options shown and filling in the boxes.

'BUILD YOUR OWN SWITCH' ORDER FORMAT

Fill in boxes with selections shown for **Model Structure**, then add **Options** selections for complete model number. Allowable options are shown below each respective box. Note 'NONE' indicates box may be left empty.

Model Structure:

Series	Number of poles	Electrical functions	Actuator and terminals	Momentary for function 4
6	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
	3 Single pole 4 Double pole 5 Three pole	1 ON - OFF 5 MOM - ON 6 ON - ON 7 MOM OFF MOM 8 ON OFF MOM 9 ON OFF ON 4 ON ON ON 4* ON ON MOM 4* MOM ON MOM <small>* specify selection from 'connections/ functions' box also.</small>	(NONE) H Metal actuator, screw terminals H / 2 Metal actuator, solder lug/quick connect style terminals N H Insulated actuator, screw terminals N H / 2 Insulated actuator, solder lug/quick-connect style terminals	(NONE) 1 R ON ON MOM 2 R MOM ON MOM

Options:

Misc. options

- (NONE)
- T High temperature DAP case: -40°C to +85°
- G Matte black finish on actuator, bushing & nuts. Includes option 'T' above.
- K Front panel sealing with 'O'-ring and sealing washer

Locking actuators

- (NONE)
 - 1 V Locking (1 position)
 - 2 V Locking (2 positions)
 - 3 V Locking (3 positions)
- (see actuator drawings).


Example of completely specified model number:
644H/21RGK

Although most combinations of options are available, some may result in incompatibilities. Consult factory if there is any question.

OPTIONS & SPECIAL OPTIONS


LOCKING ACTUATORS for 1 & 2 pole models

Arrow indicates keyway



SPECIAL OPTIONS

- T High temperature diallyl phthalate case (-40°C to +85°C).
- G Matte black finish on actuator, bushing and nuts. Includes option T above.
- K Front panel sealing with 'O'-ring and sealing washer.



K


SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

600H & 600NH SERIES - POWER TOGGLE SWITCHES


A

OPTIONS & MISCELLANEOUS


GROUNDING LUG RING



TERMINALS



600H/2 Solder lug terminals




600H Screw terminals

POSITIONS & CONNECTIONS for function 4 switches

FUNCTION 4

ACTUATOR




CONTACTS



FUNCTION 41R

ACTUATOR




CONTACTS



FUNCTION 42R

ACTUATOR




CONTACTS




MOM = momentary action


WIRING FOR 3 WAY SWITCH for function 4 switches



PANEL CUT-OUTS



SWITCH ACTION



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE