

- [Check Distributor Inventory](#)
- [Find Authorized Distributors](#)

## . My Account

- [Sign In](#)
- [Register](#)


## . Customer Support

- [Support](#)
- [RoHS Support Center](#)
- [Glossary of Terms](#)
- [eBulletin Newsletter](#)

[Home](#) > [Products](#) > [By Type](#) > [Product Feature Selector](#) > Product Details

# 8-61060-1 Product Details

 **Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



8-61060-1



### Quick Disconnect Receptacles - Insulated



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Proprietary Name = PIDG FASTON
- Receptacle Style = Straight
- Wire Range = 0.30-0.90<sup>2</sup> [22-18] mm [AWG]
- Tab Fit = 2.79 x 0.51 mm
- Insulation Diameter = 2.54 [.100] Max. mm [in]

[View all Features](#) | [Find Similar Products](#)

#### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

#### Documentation & Additional Information

**Product Drawings:**

- [RECEPTACLE, 110 SERIES, FASTON , PIDG , WIRE SIZE: 22-18](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- [FASTON TERMINALS \(INSULATED & UNINSULATED\)](#) (PDF, English)
- [STANDARD TERMINALS AND SPLICES](#) (PDF, English)

**Product Specifications:**

- [Terminal, FASTON, PIDG and PLASTI-GRIP](#) (PDF, English)

**Application Specifications:**

- [Pre-Insulated Diamond Grip \(PIDG\) FASTON Receptacle ...](#) (PDF, English)

**Instruction Sheets:**

- [APPLICATION AND MAINTENANCE FOR AMP\\* CRIMPING HEAD A...](#) (PDF, English)
- [Crimping Die Assemblies 90240-2, 90248-2, and 90280-1](#) (PDF, English)

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version N1)
- [3D Model](#) (IGES, Version N1)
- [3D Model](#) (STEP, Version N1)

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

[List all Documents](#)

**Product Features (Please use the Product Drawing for all design activity)****Product Type Features:**

- [Proprietary Name](#) = PIDG FASTON
- [Receptacle Style](#) = Straight
- [Tab Fit \(mm \[in\]\)](#) = 2.79 x 0.51 [.110 x .020]
- [Insulation Diameter \(mm \[in\]\)](#) = 2.54 [.100] Max.
- [Insertion Force](#) = Normal
- [Material](#) = Brass
- [Finish](#) = Tin
- [Dimple Type](#) = No dimple with wire stop
- Insulation Support = Insulation Support
- RU (UL Component Program) = No
- CSA Certified = No
- Color = Transparent
- Insulation Material = Nylon

**Electrical Characteristics:**

- Voltage (VAC) = 300

**Body Related Features:**

- [Fully Insulated](#) = No
- [Wire Range \(mm \[AWG\]\)](#) = 0.30-0.90<sup>2</sup> [22-18]
- Wire Range (CMA) = 509 – 1,900
- Stock Thickness (mm [in]) = 0.30 [0.012]

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

**Packaging Related Features:**

- [Packaging Method](#) = Loose Piece
- Packaging Quantity = 100/Box

**Other:**

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved