

Distributed by:

JAMECO[®]
ELECTRONICS

www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Jameco Part Number 302800



PIDG Terminals

PIDG Ring Tongue Terminals

Material and Finish

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152,
tin plated per MIL-T-10727

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers
						Loose Piece
26-22 202-810 [0.10-0.41]	0.51 .020	2 M2	3.56 .140	Yellow	2.08 .082	323912*
		4	5.16 .203	Yellow	2.08 .082	323914*
		6 M3.5	5.16 .203	Yellow	2.08 .082	323915*
		8 M4	6.35 .250	Yellow	2.08 .082	323916*
		10	6.35 .250	Yellow	2.08 .082	324075*
22-16 509-3,260 [0.26-1.65]	0.84 .033	2 M2	5.54 .218	Red	3.18 .125	328657*
		4	5.54 .218	Red	3.56 .140	31880*
		6 M3.5	7.14 .281	Red	3.56 .140	36152*
		8 M4	7.92 .312	Red	3.56 .140	31890*
		10	7.92 .312	Red	3.56 .140	36154*
		1/4 M6	11.91 .469	Red	3.56 .140	31894*
		5/16 M8	11.91 .469	Red	3.56 .140	31895*
3/8	13.49 .531	Red	3.56 .140	31897*		
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	4	6.35 .250	Blue	4.32 1.70	328996*
		6 M3.5	6.35 .250	Blue	4.32 1.70	320619*
		8 M4	8.71 .343	Blue	4.32 1.70	320565*
		10	8.71 .343	Blue	4.32 1.70	36160*
		1/4 M6	11.91 .469	Blue	4.32 1.70	321045*
		5/16 M8	11.91 .469	Blue	4.32 1.70	328998*
3/8	13.49 .531	Blue	4.32 1.70	328999*		
16-14D [†] 2,050-5,180 [1.04-2.62]	1.27 .050	8 M4	8.71 .343	Yellow/Blk.	5.84 .230	320627*
		10	8.71 .343	Yellow/Blk.	5.84 .230	320630*



*Available in small packaging quantities.
†Heavy duty for extra mechanical strength.



PIDG Terminals (Continued)

PIDG Ring Tongue Terminals (Continued)

Material and Finish

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152, tin plated per MIL-T-10727

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	6	7.14	Yellow	6.35	35149*
		M3.5	.281			
		8	9.53			
		M4	.375			
		10	9.53			
		M6	.531			
		15/16	13.49			
		M8	.531			
3/8	15.06	Yellow	6.35	35112*		
M12	.750					
1/2	19.05	Yellow	6.35	35151*		
M12	.750					



*Available in small packaging quantities.

PIDG Spade Tongue Terminals


Material and Finish

Insulation — Nylon

Terminal Body and Metallic

Sleeve — Copper per ASTM B-152, tin plated per MIL-T-10727

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dim. W	Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
22-16 509-3,260 [0.26-1.65]	0.84 .033	2	4.62	Red	3.56	328394*
		M2	.182			
		4	5.54			
		M3.5	.250			
		6	6.35			
16-14 2,050-5,180 [1.04-2.62]	0.84 .033	8	9.53	Red	3.56	32053*
		M4	.375			
		10	9.53			
		M4	.385			
		10	9.78			
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	6	7.54	Blue	4.32	35559*
		M3.5	.297			
		8	9.78			
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	8	9.78	Blue	4.32	32059*
		M4	.385			
		10	9.78			
12-10 5,180-13,100 [2.62-6.64]	1.07 .042	10	10.31	Yellow	5.84	32589*
		M6	.531			
		10	10.31			



*Available in small packaging quantities.

Power
Terminals and Miscellaneous