

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [94512-0100](#)
Status: **Active**
Description: Quick Disconnect, High Reliability Terminal (HRT), Female for (0.50-1.00mm²) 18-24 AWG Wire, Accepts 6.35 x 0.81mm Tab , Unplated


Documents:
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Product Specification PS-94512-002 \(PDF\)](#)

General	
Product Family	Quick Disconnects
Series	94512
Crimp Quality Equipment	Yes
Insulated	No
Product Name	N/A
Type	Quick Disconnect
UPC	800753536098
Physical	
Barrel Type	Open
Gender	Female
Glow-Wire Compliant	No
Insulation	None
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Unplated
Material - Plating Termination	Tin
Net Weight	0.716/g
Orientation	Straight
Packaging Type	Reel
Polarized to Mating Part	Yes
Tab Thickness	0.81mm
Tab Width	6.35mm
Temperature Range - Operating	-25°C to +55°C
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	3.30mm max.
Wire Size AWG	18, 20, 22, 24
Wire Size mm ²	0.50 - 1.00

Electrical	
Voltage - Maximum	250V

Material Info

Reference - Drawing Numbers	
Product Specification	PS-94512-002
Sales Drawing	SD-94512-004



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[94512Series](#)

Use With
[94090](#) Quick Disconnect Housing

Application Tooling FAQ	
<i>Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.</i>	
Global	
Description	Product #
Hand Crimp Tool for Quick Disconnect, High Reliability Terminal (HRT)	0638236300
Mini-Mac™	0638060600
Applicator Rear Feed	
Mini-Mac™	0638060800
Applicator Rear Feed	

This document was generated on 07/30/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION