

Search:

Select Location:

[Enclosures](#) | [Contract Manufacturing](#) | [Products](#) | [Company info](#) | [News & Events](#) | [Contacts](#) | [Downloads](#)

Product card: PC 25/22-FC3

Sample photo

Including: Base, terminal compartment cover with EPDM gasket and screws for mounting plate/DIN-rail. -3 and -L3 versions: Transparent cover with PUR gasket, hinges, locking devices; FC version: Closed PC frame front plate with PUR gasket and cover screws.

Support items:[Dimensional drawing \(inch\)](#)[Dimensional drawing \(mm\)](#)[Accessories](#)

Product nbr: 7520241
 Description: Enclosure, PC
 Remarks: With front plate frame
 Package: 1
 Unit: PCS
 Product group: CARDMASTER
 EAN: 6418074059376

Dimensions:

Length (mm): 257
 Width (mm): 219
 Height (mm): 135
 Length (inch): 10.1
 Width (inch): 8.6
 Height (inch): 5.3

Materials:

Material: Polycarbonate
 Base colour: RAL 7035
 Gasket material: EPDM and Polyurethane

Temperatures:

Min temperature °C (short term): -40
 Max temperature °C (short term): 120
 Min temperature °C (continuous): -40
 Max temperature °C (continuous): 80
 Min temperature °F (short term): -40
 Max temperature °F (short term): 250
 Min temperature °F (continuous): -40
 Max temperature °F (continuous): 175

Rating:

Ingress Protection (EN 60529):	IP 65
Impact Resistance (EN 50102):	IK 08/07
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	Yes
UV resistance:	UL 508
Flammability Rating (UL 746 C 5):	UL 94 5V
Glow Wire Test (IEC 695-2-1) °C:	960
NEMA Class:	NEMA 1, 3, 3R, 4X, 12, 13

Certificates:

Underwriters Laboratories
Fimko
Europe EN 50298: 1998
UL Canada
Gost R

Product is connected to following catalogs:

[Fibox catalogue](#) : [CARDMASTER](#) : [PC/ABS 25/22](#)

[Enclosure](#)

[search](#)

[Back to catalog](#)

[Legal Notice](#)



