



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. BERYLLIUM COPPER PER QQ-C-530
5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

1. CRIMPED FERRULE
HEX CRIMP SIZE .128"
2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	6/1	ISSUE	A	FILE NO.
6	FERRULE	COPPER	NOTE 3	1	FR-38/3X7C	DIMENSIONS ARE IN MILLIMETERS				PART NO. MMCX1112A1-3GT30G-5-50
5	COVER	NOTE 2	NOTE 3	1	CV-29X05-T	UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED DATE 10-11-01'
4	RETAINER RING	NOTE 4	NOTE 3	1	MMCX1112A1-5-C	0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				CHECKED DATE 10-11-01'
3	CONTACT PIN	NOTE 1	NOTE 5	1	MMCX1112A1-4-B					DRAWN DATE 10-11-01'
2	INSULATOR	NOTE 6	NATURAL	1	MMCX1112A1-3T-50-B					TITLE MMCX R/A CRIMP PLUG (FOR RG-174/U,188A/U,316/U)
1	HOUSING WITH BODY	NOTE 1	NOTE 3	1	MMCX1112A1-1S-23/17-B					DRAWING NO. KJ-MMCX1112A1-3GT30G-316U-50
										ITEM NO.

Amphenol