



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. BERYLLIUM COPPER PER QQ-C-530
5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

1. CRIMPED FERRULE
 HEX CRIMP SIZE .128"
 2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	6/1	ISSUE	A	FILE NO.	
6	FERRULE	COPPER	NOTE 3	1	FR-38/24X55C	DIMENSIONS ARE IN MILLIMETERS					PART NO.
5	COVER	NOTE 2	NOTE 3	1	CV-29X05-T	UNLESS OTHERWISE SPECIFIED TOLERANCES					MMCX1112A1-3GT30G-14-50
4	RETAINER RING	NOTE 4	NOTE 3	1	MMCX1112A1-5-C	0.5-6 = ±0.2					APPROVED
3	CONTACT PIN	NOTE 1	NOTE 5	1	MMCX1112A1-4-B	6-30 = ±0.4					DATE
2	INSULATOR	NOTE 6	NATURAL	1	MMCX1112A1-3T-50-B	30-120 = ±0.6					CHECKED
1	HOUSING WITH BODY	NOTE 1	NOTE 3	1	MMCX1112A1-1S-17/1-B	120-315 = ±1					DATE
						315-1000 = ±1.6					DRAWN
						1000-2000 = ±2.4					DATE

Amphenol

TITLE MMCX R/A CRIMP PLUG
(FOR RG-178B/U, 196A/U)

DRAWING NO. KJ-MMCX1112A1-3GT30G-196AU-50

ITEM NO.