

ROBUS Socket Duplicator

RKC2S

Please read instructions before commencing installation and retain for future reference.

Specification:



Bakelite resin twin switched 13A BS1363 socket outlet intended for mounting on recessed 1 gang boxes to convert 1 gang socket outlet to 2 gang socket without modification to existing wiring or building structure.

Dimensions: Width: 146mm
Height: 86mm
Projection: 22mm
Weight: (Kg) Nett: 0.170
Supply: 230/240V 50Hz
Terminal: 2 x 6mm² max
Fixing screws: 2 off M3.5x 30

Complies with BS1363

Installation:

!Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician. This fitting is designed for surface mounting on walls where a 1 gang recessed box (or dry lining box) is already installed.

- 1 Ensure mains supply is switched off
- 2 Remove unit fixing screws and their square caps from storage at back of Duplicator unit
- 3 Remove existing 1 gang socket from wall, taking note of wiring connections
- 4 Connect existing wires to same marked terminals L, N and earth on Duplicator unit
- 5 Fix Duplicator to back box securely with screws provided
- 6 Fit square caps to cover fixing screws

Duplicator unit is now ready for use.

• The installation must be carried out by an electrician. •