



**For use with: W 61, W 101, W 201**


Description and Model	Width A	Order-No. 260°C	Order-No. 310°C	Order-No. 370°C	Order-No. 425°C
-----------------------	---------	--------------------	--------------------	--------------------	--------------------


**For 60 W soldering iron (W61)**

<b>Chisel tip straight</b> 	1,6 mm	<b>CT5A5</b> 5 42 005 99	<b>CT5A6</b> 5 42 006 99	<b>CT5A7</b> 5 42 007 99	<b>CT5A8</b> 5 42 008 99
	2,4 mm	<b>CT5B5</b> 5 42 015 99	<b>CT5B6</b> 5 42 016 99	<b>CT5B7</b> ① 5 42 017 99	<b>CT5B8</b> 5 42 018 99
	3,2 mm	<b>CT5C5</b> 5 42 025 99	<b>CT5C6</b> 5 42 026 99	<b>CT5C7</b> 5 42 027 99	<b>CT5C8</b> 5 42 028 99
	5,0 mm	<b>CT5D5</b> 5 42 035 99	<b>CT5D6</b> 5 42 036 99	<b>CT5D7</b> 5 42 037 99	<b>CT5D8</b> 5 42 038 99


<b>Chisel tip bent (45°)</b> 	1,6 mm	<b>CT5AX5</b> 5 42 105 99	<b>CT5AX6</b> 5 42 106 99	<b>CT5AX7</b> 5 42 107 99	<b>CT5AX8</b> 5 42 108 99
	2,4 mm	<b>CT5BX5</b> 5 42 115 99	<b>CT5BX6</b> 5 42 116 99	<b>CT5BX7</b> 5 42 117 99	<b>CT5BX8</b> 5 42 118 99
	3,2 mm	<b>CT5CX5</b> 5 42 125 99	<b>CT5CX6</b> 5 42 126 99	<b>CT5CX7</b> 5 42 127 99	<b>CT5CX8</b> 5 42 128 99
	5,0 mm	<b>CT5DX5</b> 5 42 135 99	<b>CT5DX6</b> 5 42 136 99	<b>CT5DX7</b> 5 42 137 99	<b>CT5DX8</b> 5 42 138 99

**For 100 W soldering iron (W101)**

<b>Chisel tip straight</b> 	3,2 mm	-	<b>CT6C6</b> 5 42 206 99	<b>CT6C7</b> 5 42 207 99	<b>CT6C8</b> 5 42 208 99
	5,0 mm	-	<b>CT6D6</b> 5 42 216 99	<b>CT6D7</b> 5 42 217 99	<b>CT6D8</b> 5 42 218 99
	7,0 mm	-	<b>CT6E6</b> 5 42 226 99	<b>CT6E7</b> ① 5 42 227 99	<b>CT6E8</b> 5 42 228 99

<b>Chisel tip bent (45°)</b> 	3,2 mm	-	<b>CT6CX6</b> 5 42 306 99	<b>CT6CX7</b> 5 42 307 99	<b>CT6CX8</b> 5 42 308 99
	5,0 mm	-	<b>CT6DX6</b> 5 42 316 99	<b>CT6DX7</b> 5 42 317 99	<b>CT6DX8</b> 5 42 318 99
	7,0 mm	-	<b>CT6EX6</b> 5 42 326 99	<b>CT6EX7</b> 5 42 327 99	<b>CT6EX8</b> 5 42 328 99

**For 200 W soldering iron (W201)**

<b>Chisel tip straight</b> 	7,0 mm	-	<b>CT2E6</b> 5 42 406 99	<b>CT2E7</b> 5 42 407 99	<b>CT2E8</b> 5 42 408 99
	10,0 mm	-	<b>CT2F6</b> 5 42 416 99	<b>CT2F7</b> ① 5 42 417 99	<b>CT2F8</b> 5 42 418 99
	11,0 mm	-	<b>CT2G6</b> 5 42 426 99	<b>CT2G7</b> 5 42 427 99	<b>CT2G8</b> 5 42 428 99

<b>Chisel tip bent</b> 	7,0 mm	-	<b>CT2EX6</b> 5 42 506 99	<b>CT2EX7</b> 5 42 507 99	<b>CT2EX8</b> 5 42 508 99
	10,0 mm	-	<b>CT2FX6</b> 5 42 516 99	<b>CT2FX7</b> 5 42 517 99	<b>CT2FX8</b> 5 42 518 99

① Scope of delivery W61