

GNM214R71H471MA01#

" # " indicates a package specification code.

To be discontinued

General


125℃

Reflow OK

RoHS

< List of part numbers with package codes >  
GNM214R71H471MA01D , GNM214R71H471MA01J

Shape



|                                       |               |
|---------------------------------------|---------------|
| L size                                | 2.0 ± 0.15mm  |
| W size                                | 1.25 ± 0.15mm |
| T size                                | 0.6 ± 0.1mm   |
| Distance between external terminals P | 0.5 ± 0.05mm  |
| Size code in inch(mm)                 | 0805 (2012)   |

References

| Packaging | Specifications       | Minimum quantity |
|-----------|----------------------|------------------|
| D         | φ 180mm Paper taping | 4000             |
| J         | φ 330mm Paper taping | 10000            |

| Mass (typ.)  |      |
|--------------|------|
| 1 piece      | 11mg |
| φ 180mm Reel | 144g |

Specifications

|                                                  |             |
|--------------------------------------------------|-------------|
| Capacitance                                      | 470pF ± 20% |
| Rated voltage                                    | 50Vdc       |
| Temperature characteristics (complied standard)  | X7R(EIA)    |
| Capacitance change rate                          | ± 15.0%     |
| Temperature range of temperature characteristics | -55 to 125  |
| Operating temperature range                      | -55 to 125  |

⚠ Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.  
2.This datasheet has only typical specifications because there is no space for detailed specifications.  
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.