

GNM1M2R61C224ME18#

" # " indicates a package specification code.

References



< List of part numbers with package codes > $\mathsf{GNM1M2R61C224ME18D}\ ,\ \mathsf{GNM1M2R61C224ME18J}$

Shape

		88
L size	1.37	′±0.15mm

L size	1.37 ±0.15mm
W size	1.0 ± 0.15mm
T size	0.8 +0.0/-0.15mm
Distance between external terminals P	0.64 ± 0.05mm
Size code in inch(mm)	0504 (1410)

Specifications

Capacitance	$0.22 \mu F \pm 20\%$
Rated voltage	16Vdc
Temperature characteristics (complied standard)	X5R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 85
Operating temperature range	-55 to 85

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	4000
J	330mm Paper taping	10000

Mass (typ.)	
1 piece	4.7mg
180mm Reel	137g

1 of 1

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it 's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : http://www.murata.co.jp/

Last updated: 2014/08/18