

Technical drawing of a reel-to-reel tape cassette, showing top and side views with dimensions in inches and millimeters.

**Top View Dimensions:**

- REEL DIA. REF. (Reference diameter)
- FEED DIRECTION (Arrow pointing right)
- .500 [12.7] DIA. HOLE THRU (Central hole diameter)

**Side View Dimensions:**

- ±.005 [±0.15] (Tape thickness)
- .157 [4.0] (Tape width)
- ±.005 [±0.15] (Tape thickness)
- .059 [1.5] DIA. HOLE (TYP.) (Typical hole diameter)
- .079 [2.0] (Tape thickness)
- .787 [20.0] (Tape thickness)
- .413 [10.5] REF. (Reference dimension)
- .016 [0.4] REF. (Reference dimension)
- FEED DIRECTION (Arrow pointing right)

**Other Labels:**

- PITCH (Distance between holes)
- WIDTH (Tape width)
- NEG (Negative polarity)
- +
- 

NOTES:

### TAPE AND REEL SPECIFICATIONS:

1. TAPE:

## MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER

ANSI/EIA-481 STANDARD

1.732 [44.0] WIDE; 1.260 [32.0] PITCH

2. REEL:

13.0 [330.2] DIA. 200 PIECES OF

PART NO. 1061 PER REEL.

<b>KEYSTONE ELECTRONICS CORP.</b> ASTORIA, N.Y. 11105-2017			
PART NAME 20mm SM COIN CELL HOLDER ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY BOONE	DATE 2.28.00
		APP'D LN	SCALE X
TOLERANCES INCH [MM] DECIMAL $\pm .015$ [ $\pm 0.38$ ] ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED		CODE C/M	DWG NO. 1061TR

6.19.07	CHANGE AS PER ECN 07-037	A
DATE	DESCRIPTION	REV.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Keystone Electronics:](#)

[1061TR](#)