

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC
G

DIST
86

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	E2	REVISED PER ECO-11-004820	11MAR11	RK	HMR

AMP WIRE RANGE	FILE E66717	LR7189 Certified
22-18 AWG STRANDED	22-18 AWG STRANDED	22-18 AWG STRANDED

1

.375 REF

3

.016±.001

.21 REF

.891 MAX

1 MARKED AMP 22-18

2 DESIGNED FOR WIRE INSULATION DIA OF .090-.125.

3 MATES WITH .250±.003 BY .032±.001 THK TAB.

4 BODY: BRASS, TIN PLATED
SLEEVE: NYLON, RED

5 RATED FOR 10 MAX AMPERE

100		LOOSE PIECE	8-696357-1
1000		LOOSE PIECE	696357-1
QTY	PACKAGE TYPE	PART NO.	

TE CONNECTIVITY CUSTOMER SERVICE SYSTEM		MAX RECOMMENDED OPERATING TEMPERATURE: 105°C [221°F] -	THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN JR RUTH 07NOV01	TE Connectivity				
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWING AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752	VOLTAGE RATING: 300V MAX -	DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK T MICHELUTTI 07NOV01					
	FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .008 4 PLC ± - ANGLES ± -				APVD T MICHELUTTI 07NOV01	
			FOR ORDER ENTRY		1-800-526-5142				CIRCULAR MIL AREA: 509-1,900 STRANDED	MATERIAL - 4
					PRODUCT SPEC -	APPLICATION SPEC 114-13076	SIZE A3	CAGE CODE 00779	DRAWING NO C-696357	RESTRICTED TO -
CUSTOMER DRAWING					SCALE 1:1	SHEET 1 OF 1	REV E2			

1470-19 (3/11)