

Surface Mount Type

Series: **Medium-size TP** Type: **V**
TP High temperature Lead-Free reflow(suffix:A*)



■ Features

- Lower ESR at Low temperature after endurance
- Endurance: 3000 h at 125 °C(D8 size : 2000 h)
- Automotive
- Vibration-proof product is available upon request. ($\phi 8 \leq$)
- RoHS directive compliant

■ Specifications

Category Temp. Range	-40 °C to +125 °C																		
Rated W.V.Range	10 V.DC to 35 V.DC																		
Nominal Cap.Range	47 μ F to 470 μ F																		
Capacitance Tolerance	± 20 % (120 Hz/+20 °C)																		
DC Leakage Current	$I \leq 0.01$ CV (μ A) After 2 minutes																		
$\tan \delta$	Please see the attached standard products list																		
Endurance	After the life test with DC rated working voltage at +125 °C ± 2 °C for 3000 hours(D8 size : 2000 h), the capacitors shall meet the limits specified below.																		
	Capacitance change	± 30 % of initial measured value																	
	$\tan \delta$	≤ 300 % of initial specified value																	
	DC leakage current	\leq initial specified value																	
	ESR after Endurance ($\Omega/100$ kHz)		<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="3">Size Code</th> </tr> <tr> <th>D8</th> <th>F</th> <th>G</th> </tr> </thead> <tbody> <tr> <td>Initial(+20 °C)</td> <td>0.45</td> <td>0.2</td> <td>0.15</td> </tr> <tr> <td>After 2000 h(-40 °C)</td> <td>40</td> <td>4.5</td> <td>3.5</td> </tr> </tbody> </table>				Size Code			D8	F	G	Initial(+20 °C)	0.45	0.2	0.15	After 2000 h(-40 °C)	40	4.5
	Size Code																		
	D8	F	G																
Initial(+20 °C)	0.45	0.2	0.15																
After 2000 h(-40 °C)	40	4.5	3.5																
Shelf Life	After storage for 1000 hours at +125 °C ± 2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in Endurance (With voltage treatment)																		
Resistance to Soldering Heat	After reflow soldering and then being stabilized at +20 °C, capacitors shall meet the following limits.																		
	Capacitance change	± 10 % of initial measured value																	
	$\tan \delta$	\leq initial specified value																	
	DC leakage current	\leq initial specified value																	

■ Marking

Example: 10 V 220 μ F Marking color : BLACK

Capacitance (μ F)
 Series identification
 Mark for Lead-Free Products Black Dot (Square)
 Rated Voltage Mark
 Lot number
 Negative polarity marking (-)

A	10 V
C	16 V
E	25 V
V	35 V

■ Dimensions in mm (not to scale)

() reference size

(mm)

Size code	D	L	A, B	H max.	I	W	P	K
D8	6.3	7.7	6.6	7.8	2.6	0.65 \pm 0.1	1.8	0.35 -0.20 ~ +0.15
F	8.0	10.2	8.3	10.0	3.4	0.90 \pm 0.2	3.1	0.70 \pm 0.20
G	10.0	10.2	10.3	12.0	3.5	0.90 \pm 0.2	4.6	0.70 \pm 0.20

Standard Products

W.V. (V)	Cap. (±20 %) (μF)	Case size			Specification				Part No. (RoHS:compliant)	Reflow	Min. Packaging Q'ty
		Dia. (mm)	Length (mm)	*Size Code	Ripple Current (100 kHz) (+125 °C) (mA r.m.s.)	Impedance (100 kHz) (Ω)		tan δ (120 Hz) (+20 °C)			Taping (pcs)
						+20 °C	-40 °C				
10	220	8	10.2	F	270	0.2	3	0.30	EEETP1A221AP	(8)	500
	330	8	10.2	(F)	270	0.2	3	0.30	EEETPA331UAP	(8)	500
		10	10.2	G	500	0.15	2	0.30	EEETP1A331AP	(8)	500
	470	10	10.2	G	500	0.15	2	0.30	EEETP1A471AP	(8)	500
16	100	6.3	7.7	D8	197	0.45	5	0.23	EEETPC101XAP	(8)	900
		8	10.2	F	270	0.2	3	0.23	EEETP1C101AP	(8)	500
	220	8	10.2	F	270	0.2	3	0.23	EEETP1C221AP	(8)	500
	330	10	10.2	G	500	0.15	2	0.23	EEETP1C331AP	(8)	500
	470	10	10.2	G	500	0.15	2	0.23	EEETP1C471AP	(8)	500
25	100	8	10.2	F	270	0.2	3	0.18	EEETP1E101AP	(8)	500
	220	10	10.2	G	500	0.15	2	0.18	EEETP1E221AP	(8)	500
	330	10	10.2	G	500	0.15	2	0.18	EEETP1E331AP	(8)	500
35	47	6.3	7.7	D8	197	0.45	5	0.16	EEETPV470XAP	(8)	900
		8	10.2	F	270	0.2	3	0.16	EEETP1V470AP	(8)	500
	100	8	10.2	F	270	0.2	3	0.16	EEETP1V101AP	(8)	500
	220	10	10.2	G	500	0.15	2	0.16	EEETP1V221AP	(8)	500

* Size code():Miniaturization product

If Part number exceeds 12 digits, voltage code is abbreviated as follows; 1A→A, 1C→C, 1E→E, 1V→V

The taping dimensions are explained on p.177 of our Catalog. Please use it as a reference guide.

Reflow Profile(Fig-1 to Fig-11) listed on p.175 of our Catalog.