


PC card drilling dimensions (after plating)
[thickness 1.60±0.20mm]



		PART NUMBER				Plating: 0.76µ AU	Plating: Flash AU
SHELL	A±0.38	B±0.12	C±0.10	D±0.25			
09	30.81	24.99	16.96	16.21	D09S13B6G*00**	D09S13B4G*00**	
15	39.14	33.32	25.18	24.54	D15S13B6G*00**	D15S13B4G*00**	
25	53.03	47.04	39.12	38.25	D25S13B6G*00**	D25S13B4G*00**	
37	69.32	63.50	55.68	54.71	D37S13B6G*00**	D37S13B4G*00**	

Threaded ØT M3 = L
Threaded ØT 4.40 = X
LF FOR LEAD FREE

REQUIREMENTS

Technical characteristics
 Shell: steel tin/Zinc Cr3 plated
 Insulators: self-extinguishing black polyester, UL Class 94V0
 Contacts size 20: brass, gold 0.76µ on mating end, bright tin on termination end and over nickel on entire contact
 Cycles: 200 for plating 4
 500 for plating 6
 Harpoons: phosphor bronze, tin plated
 Metal plate for electrical continuity: brass, tin/Zinc Cr3 plated
 Nuts: brass, tin/Zinc Cr3 plated
Electrical characteristics
 max. current rating: 5A
 Test voltage: 1000V
 Rated voltage: 300V
 Contact resistance: <15mΩ
 Shell resistance: <5mΩ
 Insulation resistance: >5000MΩ
Climatic characteristics
 Operating temperature range: -55°C +125°C
Dimensions
 In accordance with MIL-C-24308

FOR ROHS DETAILS REFER DWG. NO: C01-8646-0000

European Views

www.fciconnect.com			surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	JOHN SLEEBA	1994/08/01	ANGULAR	0.X ±0.1	size A3 Scale 1:1
Eng	GEORGE VJ	1994/08/01	L LINEAR	0.XX ±0.1	
Chr	GEORGE VJ	2005/07/27	0.XX ±1*	0.XXX ±0.1	ECN -
Appr	KVSD	2005/07/27	Product family	D-SUB	Spec ref -
FCi			title SOCKET CONNECT. DELTA D RIGHT ANGLED WITH NUT, HARPOON & METAL PLATE		Rev. E
catalog no			DELTA-D		sheet 1 of 1
drawing no			C01-8646-0295		
CUSTOMER					

REV	ECN NO	DR	DATE
D	105-0124	JS	2005/07/27
E	105-0074	SK	2005/05/08
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



Copyright FCI.