

PICCOLO ABS C 65 G



Sample photo

Order symbol: ABS C 65 G
Product nbr: 8784305
Description: Enclosure, ABS
Remarks: Grey cover

EAN: 6418074002075
EI. number:
 Finland: 3423455
 Electric No. 8212001844
 Denmark:
 Electric No. Italy: 7211020
 Electric No. Sweden: 2536707

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

| Dimensions: | Length | Width | Height | Accessories: | |
|-------------|--------|-------|--------|--------------|----------------------------|
| mm: | 140 | 80 | 65 | CHM-3 | DIN-35 Mounting rail |
| inch: | 5.5 | 3.1 | 2.6 | FP 22040 | Wall fastening lug (2 pcs) |

| Materials: | Rating: |
|---|--|
| Material: ABS | Ingress Protection (EN 60529): IP66/67 |
| Base colour: RAL 7035 -light grey | Impact Resistance (EN 62262): IK07 |
| Cover screws material: Polyamide | Electrical insulation: Totally insulated |
| Cover colour: RAL 7035 -light grey | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Cover screws colour: Grey | Flammability Rating: UL 94 HB |
| Gasket material: Polyurethane | Glow Wire Test (IEC 695-2-1) °C: 650 |
| | NEMA Class: NEMA 1, 4, 4X, 6, 6P, 12, 13 |

| Temperatures: | |
|-------------------------------------|----------------|
| Temperature °C (short term): | -40 ... 80 °C |
| Temperature °C (continuous): | -40 ... 60 °C |
| Temperature °F (short term): | -40 ... 175 °F |
| Temperature °F (continuous): | -40 ... 140 °F |

| Accessories: | |
|--------------|----------------|
| C-MP | Mounting plate |

