

Crimp Terminals

Ring



RoHS
Compliant



Specifications:

Maximum Electric Current :

AWG	22	20	18	16	14	12	10
Amperes	9	12	17	18	30	35	50

Maximum Electrical Rating : 105°C 600 V

Insulation Material : Nylon


Insulation Colour : Red (22 to 16 AWG)

: Blue (16 to 14 AWG)

: Yellow (12 to 10 AWG)

Terminal Material : Copper

Double Crimp : With copper sleeve on barrel



Crimp Terminals

Ring



Part Number Table

Wire Range AWG (mm ²)	Stud Size	d2	Dimensions							Crimping Tool	Part Number
			W	F	L	E	D	d1	T		
22 to 16 (0.5 to 1.5)	#8	0.169 (4.3)	0.315 (8)	0.276 (7)	0.858 (21.8)	0.433 (11)	0.177 (4.5)	0.067 (1.7)	0.03 (0.75)	IZUMI model 34 with die index colour : red Or K.S. model KST2000B with die index colour : red	RNYDL1-4
	#6	0.146 (3.7)	0.26 (6.6)	0.248 (6.3)	0.803 (20.4)	0.433 (11)	0.177 (4.5)	0.067 (1.7)	0.03 (0.75)		RNYDM1-3.7
	#8	0.169 (4.3)	0.26 (6.6)	0.248 (6.3)	0.803 (20.4)	0.433 (11)	0.177 (4.5)	0.067 (4.5)	0.03 (0.75)		RNYDS1-4
16 to 14 (1.5 to 2.5)	5/16	0.331 (8.4)	0.472 (12)	0.433 (11)	1.094 (27.8)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031 (0.8)	IZUMI model 34 with die index colour : blue Or K.S. model KST2000B with die index colour : blue	RNYD2-8
	#10	0.209 (5.3)	0.374 (9.5)	0.327 (8.3)	1.024 (26)	0.512 (13)	0.276 (7)	0.134 (3.4)	0.039 (1)		RNYD5-5
	#4	0.126 (3.2)	0.26 (6.6)	0.189 (4.8)	0.74 (18.8)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031 (0.8)	IZUMI model 34 with die index colour : red Or K.S. model KST2000B with die index colour : red	RNYD2-3.2
	1/4	0.252 (6.4)	0.472 (12)	0.433 (11)	1.094 (27.8)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031 (0.8)		RNYD2-6
	#8	0.169 (4.3)	0.26 (6.6)	0.248 (6.3)	0.803 (20.4)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031 (0.8)		RNYDS2-4
	#6	0.146 (3.7)	0.26 (6.6)	0.248 (6.3)	0.803 (20.4)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031 (0.8)		RNYDM2-3.7
	#8	0.169 (4.3)	0.335 (8.5)	0.307 (7.8)	0.898 (22.8)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031 (0.8)		RNYDL2-4
	#10	0.209 (5.3)	0.374 (9.5)	0.287 (7.3)	0.898 (22.8)	0.433 (11)	0.205 (5.2)	0.091 (2.3)	0.031		RNYDL2-5
12 to 10 (4 to 6)	5/16	0.331 (8.4)	0.591 (15)	0.524 (13.3)	1.339 (34)	0.512 (13)	0.276 (7)	0.134 (3.4)	0.039 (1)	IZUMI model 5 with die index col- our : yellow Or K.S. model KST2000B with die index colour : yellow	RNYD5-8

Crimp Terminals

Ring



Part Number Table

Wire Range AWG (mm ²)	Stud Size	d2	Dimensions							Crimping Tool	Part Number
			W	F	L	E	D	d1	T		
12 to 10 (4 to 6)	#6	0.146 (3.7)	0.283 (7.2)	0.24 (6.1)	0.894 (22.7)	0.512 (13)	0.276 (7)	0.134 (3.4)	0.039	IZUMI model 34 with die index colour : blue Or K.S. model KST2000B with die index colour : blue	RNYD5-3.7
	#10	0.209 (5.3)	0.374 (9.5)	0.327 (8.3)	1.024 (26)	0.512 (13)	0.276 (7)	0.134 (3.4)	0.039 (1)		RNYD5-5
	1/4	0.252 (6.4)	0.472 (12)	0.413 (10.5)	1.161 (29.5)	0.512 (13)	0.276 (7)	0.134 (3.4)	0.039 (1)		RNYD5-6
	#8	0.169 (4.3)	0.283 (7.2)	0.24 (6.1)	0.894 (22.7)	0.512 (13)	0.276 (7)	0.134 (3.4)	0.039 (1)		RNYDS5-4
22 to 16 (0.5 to 1.5)	#4	0.126 (3.2)	0.217 (5.5)	0.197 (5)	0.728 (18.5)	0.433 (11)	0.177 (4.5)	0.067 (1.7)	0.03 (0.75)	IZUMI model 34 with die index colour : red Or K.S. model KST2000B with die index colour : red	RNYD1-3.2
	#10	0.209 (5.3)	0.315 (8)	0.276 (7)	0.858 (21.8)	0.433 (11)	0.177 (4.5)	0.067 (1.7)	0.03 (0.75)		RNYD1-5
	1/4	0.252 (6.4)	0.457 (11.6)	0.433 (11)	1.094 (27.8)	0.433 (11)	0.177 (4.5)	0.067 (1.7)	0.03 (0.75)		RNYD1-6
	5/16	0.331 (8.4)	0.457 (11.6)	0.433 (11)	1.094 (27.80)	0.433 (11)	0.177 (4.5)	0.067 (1.7)	0.03 (0.75)		RNYD1-8

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com

